

# SAFETY DATA SHEET



## Car Brite™ CB SELECT POLYMER SEALANT

Version 4.0      Revision Date: 07/15/2019      SDS Number: 600000000680      Date of last issue: 09/06/2018  
Date of first issue: 05/23/2016

---

### SECTION 1. IDENTIFICATION

Product name : CB SELECT POLYMER SEALANT 6/32OZ  
Product code : CBOOB106-02

#### Manufacturer or supplier's details

Company name of supplier : Niteo Products, LLC  
Address : Dallas TX 75225  
Email Address : EHS@niteoproducts.com  
Telephone : 1-844-696-4836  
Emergency telephone number : 1-800-424-9300 / 1-703-741-5970

#### Recommended use of the chemical and restrictions on use

Recommended use : POLISH  
Restrictions on use : Use only outdoors or in a well-ventilated area.



---

### SECTION 2. HAZARDS IDENTIFICATION

#### GHS classification in accordance with 29 CFR 1910.1200

Flammable liquids : Category 3  
Skin irritation : Category 2  
Skin sensitisation : Category 1  
Specific target organ toxicity - single exposure : Category 3 (Central nervous system)

#### GHS label elements

Hazard pictograms :  

Signal word : Warning

Hazard statements : Flammable liquid and vapour.  
Causes skin irritation.  
May cause an allergic skin reaction.  
May cause drowsiness or dizziness.

# SAFETY DATA SHEET



## Car Brite™ CB SELECT POLYMER SEALANT

Version 4.0      Revision Date: 07/15/2019      SDS Number: 600000000680      Date of last issue: 09/06/2018  
Date of first issue: 05/23/2016

### Precautionary statements

#### Prevention:

Keep away from heat/sparks/open flames/hot surfaces. No smoking.  
Keep container tightly closed.  
Ground/bond container and receiving equipment.  
Use explosion-proof electrical/ ventilating/ lighting equipment.  
Use only non-sparking tools.  
Take precautionary measures against static discharge.  
Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.  
Wash skin thoroughly after handling.  
Use only outdoors or in a well-ventilated area.  
Contaminated work clothing should not be allowed out of the workplace.  
Wear protective gloves/ eye protection/ face protection.

#### Response:

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.  
IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.  
If skin irritation or rash occurs: Get medical advice/ attention.  
Take off contaminated clothing and wash before reuse.  
In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

#### Storage:

Store in a well-ventilated place. Keep container tightly closed.  
Store in a well-ventilated place. Keep cool.  
Store locked up.

#### Disposal:

Dispose of contents/ container to an approved waste disposal plant.

### Other hazards

None known.

## SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

### Hazardous components

Chemical name	CAS-No.	Concentration (% w/w)
Distillates (petroleum)	64742-47-8	>= 10 - < 20
Distillates (petroleum)	64742-47-8	>= 5 - < 10
Isopropanol	67-63-0	>= 1 - < 5
Hexahydro-1,3,5-tris(2-hydroxyethyl)-s-triazine	4719-04-4	>= 0.1 - < 1
Amylcinnamaldehyde	122-40-7	>= 0.1 - < 1

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

## SECTION 4. FIRST AID MEASURES

## Car Brite™ CB SELECT POLYMER SEALANT

Version	Revision Date:	SDS Number:	Date of last issue: 09/06/2018
4.0	07/15/2019	600000000680	Date of first issue: 05/23/2016

---

- General advice : Move out of dangerous area.  
Show this safety data sheet to the doctor in attendance.  
Do not leave the victim unattended.
- If inhaled : Move to fresh air.  
Consult a physician after significant exposure.  
If unconscious, place in recovery position and seek medical advice.  
If symptoms persist, call a physician.
- In case of skin contact : If on clothes, remove clothes.  
Remove contaminated clothing. If irritation develops, get medical attention.  
If on skin, rinse well with water.  
Wash contaminated clothing before re-use.  
If skin irritation persists, call a physician.
- In case of eye contact : Flush eyes with water as a precaution.  
Remove contact lenses.  
Protect unharmed eye.  
Keep eye wide open while rinsing.
- If swallowed : Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.  
If symptoms persist, call a physician.
- Most important symptoms and effects, both acute and delayed : Causes skin irritation.  
May cause an allergic skin reaction.  
May cause drowsiness or dizziness.

---

### SECTION 5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Water spray  
Carbon dioxide (CO<sub>2</sub>)  
Dry chemical  
Alcohol-resistant foam
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during fire-fighting : Do not allow run-off from fire fighting to enter drains or water courses.
- Hazardous combustion products : Carbon oxides  
Silicon oxides
- Specific extinguishing methods : Product is compatible with standard fire-fighting agents.
- Further information : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.  
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.  
Use a water spray to cool fully closed containers.
- Special protective equipment : In the event of fire, wear self-contained breathing apparatus.

## Car Brite™ CB SELECT POLYMER SEALANT

Version	Revision Date:	SDS Number:	Date of last issue: 09/06/2018
4.0	07/15/2019	600000000680	Date of first issue: 05/23/2016

for firefighters

### SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.  
Remove all sources of ignition.  
Avoid breathing dust.  
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.  
Evacuate personnel to safe areas.  
Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.
- Environmental precautions : Prevent further leakage or spillage if safe to do so.  
Prevent product from entering drains.  
Do not flush into surface water or sanitary sewer system.  
If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods and materials for containment and cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

### SECTION 7. HANDLING AND STORAGE

- Advice on protection against fire and explosion : Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours).  
Electrically bond and ground all containers, personnel and equipment before transfer or use of material. Special precautions may be necessary to dissipate static electricity for non-conductive containers. Use proper bonding and grounding during product transfer as described in National Fire Protection Association document NFPA 77.  
Keep away from open flames, hot surfaces and sources of ignition.  
Use only explosion-proof equipment.  
Do not spray on a naked flame or any incandescent material.
- Advice on safe handling : Open drum carefully as content may be under pressure.  
Avoid formation of aerosol.  
Provide sufficient air exchange and/or exhaust in work rooms.  
Do not breathe vapours/dust.  
Do not smoke.  
Take precautionary measures against static discharges.  
Avoid contact with skin and eyes.  
Persons susceptible to skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.  
Dispose of rinse water in accordance with local and national regulations.  
Container hazardous when empty.  
Smoking, eating and drinking should be prohibited in the application area.

## Car Brite™ CB SELECT POLYMER SEALANT

Version 4.0      Revision Date: 07/15/2019      SDS Number: 600000000680      Date of last issue: 09/06/2018  
Date of first issue: 05/23/2016

For personal protection see section 8.

Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated place.  
Containers which are opened must be carefully resealed and kept upright to prevent leakage.  
Observe label precautions.  
No smoking.

Further information on storage stability : No decomposition if stored and applied as directed.

## SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

## Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Distillates (petroleum)	64742-47-8	TWA (Mist)	5 mg/m <sup>3</sup>	OSHA Z-1
		TWA	200 mg/m <sup>3</sup> (total hydrocarbon vapor)	ACGIH
		TWA (Mist)	5 mg/m <sup>3</sup>	OSHA P0
		TWA (Mist)	5 mg/m <sup>3</sup>	NIOSH REL
		ST (Mist)	10 mg/m <sup>3</sup>	NIOSH REL
Distillates (petroleum)	64742-47-8	TWA (Mist)	5 mg/m <sup>3</sup>	OSHA Z-1
		TWA	200 mg/m <sup>3</sup> (total hydrocarbon vapor)	ACGIH
		TWA (Mist)	5 mg/m <sup>3</sup>	OSHA P0
		TWA (Mist)	5 mg/m <sup>3</sup>	NIOSH REL
		ST (Mist)	10 mg/m <sup>3</sup>	NIOSH REL
Isopropanol	67-63-0	TWA	200 ppm	ACGIH
		STEL	400 ppm	ACGIH
		TWA	400 ppm 980 mg/m <sup>3</sup>	NIOSH REL
		ST	500 ppm 1,225 mg/m <sup>3</sup>	NIOSH REL
		TWA	400 ppm 980 mg/m <sup>3</sup>	OSHA Z-1
		TWA	400 ppm 980 mg/m <sup>3</sup>	OSHA P0
		STEL	500 ppm 1,225 mg/m <sup>3</sup>	OSHA P0

## Hazardous components without workplace control parameters

Components	CAS-No.
Hexahydro-1,3,5-tris(2-hydroxyethyl)-s-triazine	4719-04-4
Amylcinnamaldehyde	122-40-7

## Car Brite™ CB SELECT POLYMER SEALANT

Version 4.0      Revision Date: 07/15/2019      SDS Number: 600000000680      Date of last issue: 09/06/2018  
 Date of first issue: 05/23/2016

### Biological occupational exposure limits

Components	CAS-No.	Control parameters	Biological specimen	Sam-pling time	Permissible concentra-tion	Basis
Isopropanol	67-63-0	Acetone	Urine	End of shift at end of work-week	40 mg/l	ACGIH BEI

**Engineering measures** : Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

### Personal protective equipment

Respiratory protection : In the case of vapour formation use a respirator with an approved filter.

Hand protection

Remarks : Wear resistant gloves (consult your safety equipment supplier). The suitability for a specific workplace should be discussed with the producers of the protective gloves. Discard gloves that show tears, pinholes, or signs of wear.

Eye protection : Not required under normal conditions of use. Wear splash-proof safety goggles if material could be misted or splashed into eyes.

Skin and body protection : Choose body protection according to the amount and concentration of the dangerous substance at the work place.  
 Wear as appropriate:  
 Impervious clothing  
 Flame-resistant clothing  
 Safety shoes

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice.  
 When using do not smoke.  
 When using do not eat or drink.

## SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid  
 Colour : light green  
 Odour : fruity  
 Odour Threshold : No data available  
 pH : 8.5  
 Melting point/freezing point : 0 °C

# SAFETY DATA SHEET



## Car Brite™ CB SELECT POLYMER SEALANT

Version 4.0      Revision Date: 07/15/2019      SDS Number: 600000000680      Date of last issue: 09/06/2018  
Date of first issue: 05/23/2016

---

Boiling point/boiling range : 35 °C  
(1,013 hPa)  
The value is calculated

Flash point : 40 °C  
Method: Tag closed cup

Evaporation rate : No data available

Flammability (solid, gas) : No data available

Self-ignition : No data available

Upper explosion limit / Upper flammability limit : 12 %(V)  
The value is calculated

Lower explosion limit / Lower flammability limit : 0.6 %(V)  
The value is calculated

Vapour pressure : 60.53 hPa (25 °C)  
The value is calculated

Relative vapour density : No data available

Density : 0.956 g/cm<sup>3</sup> (60 °C)

Solubility(ies)  
Water solubility : partly soluble

Partition coefficient: n-octanol/water : No data available

Decomposition temperature : not determined

Viscosity  
Viscosity, dynamic : No data available

Viscosity, kinematic : > 10000 mm<sup>2</sup>/s (40 °C)

Oxidizing properties : No data available

Molecular weight : Not applicable

---

### SECTION 10. STABILITY AND REACTIVITY

Reactivity : No decomposition if stored and applied as directed.

Chemical stability : No decomposition if stored and applied as directed.

Possibility of hazardous reactions : No decomposition if stored and applied as directed.  
Vapours may form explosive mixture with air.

Conditions to avoid : Heat, flames and sparks.

Incompatible materials : Acids  
Aldehydes

**Car Brite™ CB SELECT POLYMER SEALANT**

Version	Revision Date:	SDS Number:	Date of last issue: 09/06/2018
4.0	07/15/2019	600000000680	Date of first issue: 05/23/2016

Bases  
Amines  
Ethylene oxide  
Halogenated compounds  
isocyanates  
Strong oxidizing agents  
Strong reducing agents

Hazardous decomposition products : Carbon oxides  
Silicon oxides

**SECTION 11. TOXICOLOGICAL INFORMATION****Information on likely routes of exposure**

Inhalation  
Skin contact  
Eye contact  
Ingestion

**Acute toxicity**

Not classified based on available information.

**Product:**

Acute inhalation toxicity : Acute toxicity estimate: 124.55 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist  
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: > 5,000 mg/kg  
Method: Calculation method

**Components:****Distillates (petroleum):**

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat, male and female): Exposure time: 4 h  
Test atmosphere: vapour  
Method: OECD Test Guideline 403  
Assessment: No adverse effect has been observed in acute inhalation toxicity tests.

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg  
Assessment: No adverse effect has been observed in acute dermal toxicity tests.

**Isopropanol:**

Acute oral toxicity : LD50 (Rat): 5.84 g/kg

Acute inhalation toxicity : LC50 (Rat): 16000 ppm  
Exposure time: 4 h  
Test atmosphere: vapour

Acute dermal toxicity : LD50 (Rabbit): 12,800 mg/kg



**Car Brite™ CB SELECT POLYMER SEALANT**

Version	Revision Date:	SDS Number:	Date of last issue: 09/06/2018
4.0	07/15/2019	600000000680	Date of first issue: 05/23/2016

---

**Hexahydro-1,3,5-tris(2-hydroxyethyl)-s-triazine:**

Acute oral toxicity : LD50 (Rat, male and female): 1,000 mg/kg  
Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50 (Rat): 0.371 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist

Acute dermal toxicity : LD50 (Rat): > 4,000 mg/kg  
Assessment: No adverse effect has been observed in acute dermal toxicity tests.

**Amylcinnamaldehyde:**

Acute oral toxicity : LD50 (Rat): 3,730 mg/kg

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg  
Assessment: No adverse effect has been observed in acute dermal toxicity tests.

**Skin corrosion/irritation**

Causes skin irritation.

**Product:**

Remarks: May cause skin irritation and/or dermatitis.

**Components:****Distillates (petroleum):**

Result: Irritating to skin.

**Distillates (petroleum):**

Result: Repeated exposure may cause skin dryness or cracking.

**Isopropanol:**

Result: Possibly irritating to skin

**Hexahydro-1,3,5-tris(2-hydroxyethyl)-s-triazine:**

Method: OECD Test Guideline 404  
Result: No skin irritation

**Amylcinnamaldehyde:**

Result: Irritating to skin.  
Remarks: Information given is based on data obtained from similar substances.

**Serious eye damage/eye irritation**

Not classified based on available information.

**Product:**

Remarks: Vapours may cause irritation to the eyes, respiratory system and the skin.

**Car Brite™ CB SELECT POLYMER SEALANT**

Version      Revision Date:      SDS Number:      Date of last issue: 09/06/2018  
4.0          07/15/2019          600000000680      Date of first issue: 05/23/2016

---

**Components:****Distillates (petroleum):**

Result: Possibly irritating to eyes

**Isopropanol:**

Result: Irritating to eyes.

**Hexahydro-1,3,5-tris(2-hydroxyethyl)-s-triazine:**

Result: Irritating to eyes.

Method: OECD Test Guideline 405

**Amylcinnamaldehyde:**

Result: Irritating to eyes.

Remarks: Information given is based on data obtained from similar substances.

**Respiratory or skin sensitisation****Skin sensitisation**

May cause an allergic skin reaction.

**Respiratory sensitisation**

Not classified based on available information.

**Product:**

Remarks: May cause allergic skin reaction.

**Components:****Hexahydro-1,3,5-tris(2-hydroxyethyl)-s-triazine:**

Species: Guinea pig

Result: May cause sensitisation by skin contact.

**Amylcinnamaldehyde:**

Assessment: May cause sensitisation by skin contact.

Remarks: Information given is based on data obtained from similar substances.

**Germ cell mutagenicity**

Not classified based on available information.

**Carcinogenicity**

Not classified based on available information.

**IARC**

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

**OSHA**

No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

**NTP**

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen

# SAFETY DATA SHEET



## Car Brite™ CB SELECT POLYMER SEALANT

Version	Revision Date:	SDS Number:	Date of last issue: 09/06/2018
4.0	07/15/2019	600000000680	Date of first issue: 05/23/2016

---

by NTP.

### **Reproductive toxicity**

Not classified based on available information.

### **STOT - single exposure**

May cause drowsiness or dizziness.

### **Components:**

#### **Distillates (petroleum):**

Assessment: May cause drowsiness or dizziness.

#### **Distillates (petroleum):**

Target Organs: Central nervous system

Assessment: May cause drowsiness or dizziness.

#### **Isopropanol:**

Assessment: May cause drowsiness or dizziness.

### **STOT - repeated exposure**

Not classified based on available information.

### **Components:**

#### **Hexahydro-1,3,5-tris(2-hydroxyethyl)-s-triazine:**

Exposure routes: Inhalation

Target Organs: Respiratory system

Assessment: Causes damage to organs through prolonged or repeated exposure.

### **Aspiration toxicity**

Not classified based on available information.

### **Product:**

No aspiration toxicity classification

### **Components:**

#### **Distillates (petroleum):**

May be fatal if swallowed and enters airways.

#### **Distillates (petroleum):**

May be fatal if swallowed and enters airways.

### **Further information**

### **Product:**

Remarks: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.

## Car Brite™ CB SELECT POLYMER SEALANT

Version	Revision Date:	SDS Number:	Date of last issue: 09/06/2018
4.0	07/15/2019	600000000680	Date of first issue: 05/23/2016

### SECTION 12. ECOLOGICAL INFORMATION

#### Toxicity

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.  
Harmful to aquatic life with long lasting effects.

### SECTION 13. DISPOSAL CONSIDERATIONS

#### Disposal methods

Waste from residues : Dispose of in accordance with all applicable local, state and federal regulations.

Contaminated packaging : Empty remaining contents.  
Dispose of as unused product.  
Do not re-use empty containers.  
Do not burn, or use a cutting torch on, the empty drum.

### SECTION 14. TRANSPORT INFORMATION

Dangerous goods descriptions (if indicated below) may not reflect quantity, end-use, or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

#### International Regulations

##### IATA-DGR

UN/ID No. : UN 1993  
 Proper shipping name : Flammable liquid, n.o.s.  
 (Isopropanol, Hydrotreated Petroleum Distillates)  
 Class : 3  
 Packing group : III  
 Labels : 3  
 Packing instruction (cargo aircraft) : 366  
 Packing instruction (passenger aircraft) : 355

##### IMDG-Code

UN number : UN 1993  
 Proper shipping name : FLAMMABLE LIQUID, N.O.S.  
 (Isopropanol, Hydrotreated Petroleum Distillates)  
 Class : 3  
 Packing group : III  
 Labels : 3  
 EmS Code : F-E, S-E  
 Marine pollutant : no

#### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

#### National Regulations

##### 49 CFR



# SAFETY DATA SHEET




## Car Brite™ CB SELECT POLYMER SEALANT

Version 4.0      Revision Date: 07/15/2019      SDS Number: 600000000680      Date of last issue: 09/06/2018  
Date of first issue: 05/23/2016

### SECTION 16. OTHER INFORMATION

#### Further information

#### NFPA:



Special hazard.

Revision Date : 07/15/2019

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN