SDS No: 7013-1 Version: 1.1 (REG_29 CFR 1910.1200 /REG_GHS Rev.5th e.2013)

Date of last Revision: 08/19/2014

1.1	Product identifier used on the label: Foaming Prep Shampoo
1.2	Other means of identification: Not Applicable
1.3	Recommended use of the chemical and restrictions on use: An automotive concentrated shampoo. This material should not be used for any other purpose than that recommended without expert advice.
1.4	Name, address, and telephone number of the chemical manufacturer, importer, or other responsible party: J.B.Chemical Co., Inc. 14803 S. Spring Street Gardena, CA 90248, USA 310-532-3021 800-522-2468
1.5	Emergency phone numbers: J.B.Chemical Co., Inc.: (310) 532-3021, (800) 522-2468 Monday - Friday, 7:00am - 3:00pm PST

Chemtrec: (800) 424-9300 - Outside the continental U.S.: (703) 527-3887 24 Hours

2.Hazard(s) identification

2.1	Classification of the chemical in accordance with 29 CFR 1910.1200(d) and GHS Rev.5 th e.2013: This product is classified as hazardous.
	Eye Irritation Category 2A Skin Irritation Category 2 Specific Target Organ Toxicity Single Exposure Category 3

2.2

Signal word, hazard statement(s), symbol(s) and precautionary statement(s) in accordance with 29 CFR 1910.1200(f) and GHS Rev.5th e.2013:

Signal word: Warning

Hazard statement(s):

Physical Hazards: Not Applicable

Health Hazards: H319: Causes serious eye irritation.

H315: Cause skin irritation. H335: May cause respiratory

irritation.

Symbol(s):

Precautionary statement(s):

SDS No: 7013-1

Version: 1.1 (REG_29 CFR 1910.1200 /REG_GHS Rev.5th e.2013)

Date of last Revision: 08/19/2014

Prevention:

P102: Keep out of reach of children.

P264: Wash hands thoroughly after handling.

P261: Avoid breathing dust/fume/gas/mist/vapors/spray. P271: Use only outdoors or in a well-ventilated area.

P280: Wear protective gloves/ eye protection.

Response:

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337+P313: If eye irritation persists: Get medical advice/attention. P302+P352: IF ON SKIN: Wash with plenty of soap and water.

P332+P313: If skin irritation occurs: Get medical advice/attention.

P304+P340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. P362: Take off contaminated clothing and wash before reuse.

Storage:

P403+P233: Store in a well-ventilated place. Keep container tightly closed. P405: Store locked up.

Disposal:

P501: Dispose of contents/container in accordance with CERCLA/CWA (Section 311)/SARA Title III Regulations.

2.3	Describe any hazards not otherwise classified that have been identified during the classification process Not Applicable
2.4	Where an ingredient with unknown acute toxicity is used in a mixture at a concentration ≥ 1% and the mixture is not classified based on testing of the mixture as a whole, a statement that X% of the mixture consists of ingredient(s) of unknown acute toxicity is required: Not Applicable

Chemical name	CAS No.	EC No.	Concentration (Wt%)	Classification 29 CFR 1910.1200(d)/GHS
Sodium Dodecylbenzenesulfo nate	25155-30-0	246-680-4	≤ 25.0	Acute Tox.4 H302 Acute Tox.4 H312 Eye Irrit.2 H319 Skin Irrit.2 H315 STOT SE3 H335
Alcohols, C10-16, ethoxylated, sulfates, sodium salts	68585-34-2	500-223-8	≤ 5.00	Acute Tox.4 H302 Skin Irrit.2 H315 Eye Irrit.2 H319 STOT SE3 H335
Ethylene glycol monobutyl ether	111-76-2	203-905-0	≤ 2.50	Flam. Liq.4 H227 Acute Tox.4 H302 Acute Tox.4 H312 Skin Irrit.2 H315 Eye Irrit.2 H319 Acute Tox.4 H332 Asp Tox.1 H304

SDS No: 7013-1

Version: 1.1 (REG_29 CFR 1910.1200 /REG_GHS Rev.5th e.2013)
Date of last Revision: 08/19/2014

4.First-aid measures

4.1	Description of necessary measures, subdivided according to the different routes of exposure, i.e., inhalation, skin and eye contact, and ingestion.
	Inhalation: If respiratory symptoms develop, move victim away from source of exposure and into fresh air. If symptoms persist, get medical attention. Skin contact: Clean affected areas with mild soap and water. Remove contaminated clothing, including shoes, and launder before reuse or discard. If any irritation persists, seek medical attention. Eye contact: Immediately flush with plenty of water for at least 15 minutes. If easy to do, remove contact lenses. If any irritation persists, get medical attention. Ingestion: Do not induce vomiting or give anything by
	mouth. If victim is drowsy or unconscious, place on the left side with head down. If possible, do not leave victim unattended.
4.2	Most important symptoms/effects, acute and delayed: Eye and skin irritation.
4.3	Indication of immediate medical attention and special treatment needed, if necessary: Persistent eye and skin irritation.

5.Fire-fighting measures

5.1	Suitable (and unsuitable) extinguishing media: Foam, water spray or fog. Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only. Do not discharge extinguishing waters into the aquatic environment.
5.2	Specific hazards arising from the chemical (e.g., nature of any hazardous combustion products): Carbon monoxide may be evolved if incomplete combustion occurs. Will float and can be reignited on surface water. The vapor is heavier than air, spreads along the ground and distant ignition is possible.
5.3	Special protective equipment and precautions for fire- fighters: Wear full protective clothing and self-contained breathing apparatus.

6.Accidental release measures

6.1	Personal precautions, protective equipment, and emergency procedures: Avoid contact with spilled or released material. Immediately remove all contaminated clothing. Wear protective equipment to prevent skin and eye contact and breathing in vapors. Remove all possible sources of ignition in the surrounding area. Shut off leaks, if possible without personal risks. Use appropriate containment (of product and firefighting water) to avoid environmental contamination. Prevent from spreading or entering drains, ditches or rivers by using sand, earth, or other appropriate barriers. Attempt to disperse the vapor or to direct its flow to a safe location for example by using fog sprays. Take precautionary measures against static discharge. Ensure electrical continuity by bonding and grounding (earthing) all equipment.
6.2	Methods and materials for containment and cleaning up: For small liquid spills (< 1 drum), transfer by mechanical means to a labeled, sealable container for product recovery or safe disposal. Allow residues to evaporate or soak up with an appropriate absorbent material and dispose of safely. Remove contaminated soil and dispose of safely. For large liquid spills (> 1 drum), transfer by mechanical

SDS No: 7013-1

Version: 1.1 (REG_29 CFR 1910.1200 /REG_GHS Rev.5th e.2013)

Date of last Revision: 08/19/2014

means such as vacuum truck to a salvage tank for recovery or safe disposal. Do not flush away residues with water. Retain as contaminated waste. Allow residues to evaporate or soak up with an appropriate absorbent material and dispose of safely. Remove contaminated soil and dispose of safely.

Notify authorities if any exposure to the general public or the environment occurs or is likely to occur. U.S. regulations may require reporting releases of this material to the environment which exceed the reportable quantity (refer to Chapter 15) to the National Response Centre at (800) 424-8802.

7.Handeling and storage	
7.1	Precautions for safe handling: Avoid breathing mists or vapors. Avoid contact with eyes, skin, and clothing. Do not taste or swallow. Use only with adequate ventilation. Wash thoroughly after handling. Do not wear contaminated clothing or shoes. Handle an open container with care in a well-ventilated area. Ventilate work place in such a way that the Occupational Exposure Limit (OEL) is not exceeded. Do not empty into drains. Avoid handling above its flash point otherwise the product will form flammable/explosive vapor-air mixtures.
7.2	Conditions for safe storage, including any incompatibilities:

For small containers, keep out of reach of children. Keep tightly closed and store in a cool and well ventilated area.

Store only in approved containers and protect from physical damage. Storage should meet OSHA standards. Empty drums should be completely drained, properly bunged, and promptly shipped to a drum reconditioner. All other containers should be disposed of in an environmentally safe manner and in accordance with governmental regulation. Do not overheat; product will start boiling if heated above 200°F. Containers, even those that have been emptied, can contain explosive vapors. Do not cut, drill, grind, weld or perform similar operations on or near containers.

8.Exposure controls/ personal protection

OSHA permissible exposure limit (PEL), American Conference of Governmental Industrial Hygienists (ACGIH)
Threshold Limit Value (TLV), and any other exposure limit used or recommended by the chemical
manufacturer, importer, or employer preparing the safety data sheet, where available:
Component(s):

Chemical name	Туре	Exposure Limit values	Source
Sodium Dodecylbenzenesulfonate	TWA (vapor,8 hr)	No data available	
Alcohols, C10-16, ethoxylated, sulfates, sodium salts	TWA (vapor,8 hr)	No data available	
Ethylene glycol monobutyl ether CAS No: 111-76-2	TWA (vapor,8 hr)	20 ppm	US. ACGIH Threshold Limit Values (01 2010)

Appropriate engineering controls: Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment.

Individual protection measures, such as personal protective equipment:

SDS No: 7013-1

Version: 1.1 (REG_29 CFR 1910.1200 /REG_GHS Rev.5th e.2013)

Date of last Revision: 08/19/2014

Eye/face protection: Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended: Safety Glasses with side shields

Skin/hand protection: Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Gloves made from the following material(s) are recommended: Nitrile rubber

Respiratory protection: If engineering controls do not maintain airborne contaminant concentrations at a level which is adequate to protect worker health, an approved respirator may be appropriate. Respirator selection, use and maintenance must be in accordance with regulatory requirements. If applicable, types of respirators to be considered for this material include: half-face air-purifying filter respirator suitable for organic vapors and particulates (P95).

9. Physical and chemical properties

Appearance (physical state, color, etc.):	Liquid, red
Odor:	Cherry
Odor threshold:	Not Determined
pH:	7.0-9.0
Melting point/freezing point:	Not Applicable
Initial boiling point and boiling range:	>200 °F
Flash point:	Not Applicable
Evaporation rate:	Not Determined
Flammability (solid, gas):	Not Applicable
Upper/lower flammability or explosive limits:	Not Applicable
Vapor pressure:	Not Determined
Vapor density:	Not Determined
Relative density:	1.03 at 77°F (Water=1)
Solubility(ies):	Miscible in water
Partition coefficient: n-octanol/water:	Not Determined
Auto-ignition temperature:	Not Determined
Decomposition temperature:	Not Determined
Viscosity:	Not Determined

10.Stability and reactivity

10.1	Reactivity: This material is considered to be non-reactive under normal use conditions.
10.2	Chemical stability: Stable.
10.3	Possibility of hazardous reactions: Hazardous polymerization will not occur.
10.4	Conditions to avoid (e.g., static discharge, shock, or vibration): Avoid heat, sparks, open flames and other ignition sources.

SDS No: 7013-1

Version: 1.1 (REG_29 CFR 1910.1200 /REG_GHS Rev.5th e.2013)

Date of last Revision: 08/19/2014

10.5	Incompatible materials: Strong oxidizing agents.
10.6	Hazardous decomposition products: Thermal
	decomposition is highly dependent on conditions. A complex
	mixture of airborne solids, liquids and gases, including
	carbon monoxide, carbon dioxide and other organic
	compounds will be evolved when this material undergoes
	combustion or thermal or oxidative degradation.

Description of the various toxicological (health) effects and the available data used to identify those effects, including:

Information on the likely routes of exposure (inhalation, ingestion, skin and eye contact):

Inhalation: May cause respiratory tract irritation. Avoid breathing dust/fume/gas/mist/vapors/spray.

Ingestion: May be harmful if ingested. Causes gastrointestinal irritation with nausea, vomiting and diarrhea. May cause central nervous system depression, characterized by excitement, followed by headache, dizziness, drowsiness, and nausea. Advanced stages may cause collapse,

unconsciousness, coma and possible death due to respiratory failure.

Skin contact: Causes moderate skin irritation. **Eye contact:** Severely irritating to the eyes.

Symptoms related to the physical, chemical and toxicological characteristics: Not Determined

Delayed and immediate effects and also chronic effects from short- and long-term exposure: See section 11.1.

Numerical measures of toxicity (such as acute toxicity estimates): Not determined on the mixture.

Acute toxicity

Name (Components)	Route	Species	Value
Sodium	Dermal	Rabbit	LD50>2000 mg/m3
Dodecylbenzenesulfonate			-
CAS No: 25155-30-0			
"	Ingestion	Rat	LD50>1080 mg/kg
"	Inhalation (Aerosol,4 hours)	Rat	Moderately toxic
			(Respirable particles)
Ethylene glycol	Dermal	Rat	LD50 > 2000 mg/kg
monobutyl ether CAS			
No:111-76-2			
"	Ingestion	Rat	LD50 > 1300 mg/kg
"	Inhalation-vapor (3 hours)	Rat	LC50 > 4.9 mg/l

Skin Corrosion/Irritation

I	Name (Components)	Species	Value
	Sodium Dodecylbenzenesulfonate CAS No: 25155-30-0	Rabbit	Cause moderate skin irritation.
	Ethylene glycol monobutyl ether CAS No:111-76-2	Rabbit (24 hours)	Moderate irritation

SDS No: 7013-1

Version: 1.1 (REG_29 CFR 1910.1200 /REG_GHS Rev.5th e.2013)

Date of last Revision: 08/19/2014

Serious Eye Damage/Irritation

	-	
Name (Components)	Species	Value
Sodium Dodecylbenzenesulfonate CAS No: 25155-30-0	Rabbit	Causes severe eye irritation.
Ethylene glycol monobutyl ether CAS No:111-76-2	Rabbit (24 hours)	Moderate irritation

Respiratory or skin sensitization

Name (Components)	Species	Value
Sodium Dodecylbenzenesulfonate	Guinea pigs (Skin)	Negative
CAS No: 25155-30-0		
Ethylene glycol monobutyl ether CAS	Guinea Pig	Not a skin sensitizer
No:111-76-2		

Germ Cell Mutagenicity

Name (Components)	Route	Value
Sodium Dodecylbenzenesulfonate CAS No: 25155-30-0	In Vivo	Negative
"	In Vitro	Negative

Ethylene glycol monobutyl ether CAS No:111-76-2	In Vitro: Salmonella typhimurium assay (Ames test)	Negative +/- activation
----------------------------------------------------	----------------------------------------------------	-------------------------

Carcinogenicity

Name (Components)	Route	Species	Value
Sodium	Oral	Rat	Not classified
Dodecylbenzenesulfonate CAS No: 25155-30-0			
Ethylene glycol monobutyl ether CAS No:111-76-2			Not Classified.

Reproductive toxicity

Name (Components)	Route	Species	Value	Test Result	Exposure Duration
Sodium Dodecylbenzene sulfonate CAS No: 25155-30-0	Oral	Rat		Not classified	
Ethylene glycol monobutyl ether CAS No:111-76-2			Not Classified		

Specific Target Organ Toxicity - single exposure

Name (components)	Route	Species	Target Organ	Value	Test Result	Exposure Duration
Sodium Dodecylbenze nesulfonate CAS No: 25155-30-0				No data available		

SDS No: 7013-1 Version: 1.1 (REG_29 CFR 1910.1200 /REG_GHS Rev.5th e.2013) Date of last Revision: 08/19/2014

Ethylene	Inhalation	Central	May cause	NOAEL	
glycol		Nervous	drowsiness or		
monobutyl		System	dizziness		
ether CAS					
No:111-76-2					

Specific Target Organ Toxicity - repeated exposure

Name (components)	Route	Species	Target Organ	Value	Test Result	Exposure Duration
Sodium Dodecylbenze nesulfonate CAS No: 25155-30-0	Oral Dermal	Rodent/ non- rodent	Kindeys/ haematologic Effects/ Growth retardation		NOAEL 85 mg/kg bw/ day	9 months

Ethylene	Dermal	Rat	150	NOAEL	
glycol			mg/kg		
monobutyl					
ether CAS					
No:111-76-2					

Aspiration Hazard

Name (Components)	Value
Sodium Dodecylbenzenesulfonate CAS No: 25155-30-0	No data available
Ethylene glycol monobutyl ether CAS No:111-76-2	Aspiration Hazard Toxicity Category 1

12.Ecological information

12.1	Ecotoxicity (aquatic and terrestrial, where available): Not determined
12.2	Persistence and degradability: Not determined
12.3	Bioaccumulative potential: Not determined
12.4	Mobility in soil: Not determined
12.5	Other adverse effects (such as hazardous to the ozone layer): Not determined

13.Disposal considerations

Description of waste residues and information on their safe handling and methods of disposal, including the disposal of any contaminated packaging: Dispose of contents/ container in accordance with the local/regional/national/international regulations. Do not contaminate any lakes, streams, ponds, or underground water supplies.

Empty Container Warning Empty Container Warning (where applicable): Empty containers may contain residue and can be dangerous. Do not attempt to refill or clean containers without proper instructions. Empty drums should be completely drained and safely stored until appropriately reconditioned or disposed. Empty containers should be taken for recycling, recovery, or disposal through suitably qualified or licensed contractor and in accordance with governmental regulations. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, static electricity, or other sources of ignition. They may explode and cause injury or death.

SDS No: 7013-1

Version: 1.1 (REG_29 CFR 1910.1200 /REG_GHS Rev.5th e.2013)

Date of last Revision: 08/19/2014

14. Transport information

Because this product is produced and shipped in several different container sizes, domestically and internationally, please consult your transportation specialist for the proper shipping name and class.

14.1	UN number: Not Regulated
14.2	UN proper shipping name: Not Regulated
14.3	Transport hazard class(es): Not Regulated
14.4	Packing group, if applicable: Not Regulated
14.5	Environmental hazards (e.g., Marine pollutant (Yes/No)): Not determined
14.6	Transport in bulk (according to Annex II of MARPOL 73/78 and the IBC Code): Not determined
14.7	Special precautions which a user needs to be aware of, or needs to comply with, in connection with transport or conveyance either within or outside their premises: Not determined

15.Regulatory information

15.1

Safety, health and environmental regulations specific for the product in question:

OSHA Hazard Communication Standard: This material is classified as hazardous in accordance with OSHA 29 CFR 1910.1200 (see section 2).

TSCA: Components of this product are listed on the TSCA Inventory.

SARA Title III, Section 302 (Extremely Hazardous Substances): None

SARA Title III, Section 313: This product contains 2-Butoxyethanol (CAS No: 111-76-2 ≤ 2.50%) which is subject to the reporting requirements of SARA Title III.

SARA Title III. Section 311/312 Classifications:

Fire Hazard: No Pressure Hazard:

No Reactivity

Hazard: No

Immediate Hazard: Yes Delayed Hazard:

No

CERCLA Hazardous Substances: This material is not subject to any special reporting under the requirements of the Comprehensive Environmental Response, Compensation and Liability Act (CERCLA). Contact local authorities to determine if other reporting requirements apply.

Clean Air Act Section 112(r): None

CLEAN WATER ACT/OIL POLLUTION ACT: None CA PROP 65:

WARNING! This product contains a chemical known to the State of California to cause cancer: None WARNING! This product contains a chemical known to the State of California to cause birth defects or other reproductive harm: None

Note: The regulatory information given above only indicates the principal regulations specifically applicable to the product described in the safety data sheet. The user's attention is drawn to the possible existence of additional provisions which complete these regulations. Refer to all applicable national, international and local regulations or provisions.

SDS No: 7013-1

Version: 1.1 (REG_29 CFR 1910.1200 /REG_GHS Rev.5th e.2013)

Date of last Revision: 08/19/2014

Full text of H-Statements referred to under sections 2 and 3:

H302: Harmful if swallowed.

H312: Harmful in contact with skin.

H315: Causes skin irritation.

H319: Causes serious eye irritation. H335:

May cause respiratory irritation. H332:

Harmful if inhaled.

H336: May cause drowsiness or dizziness.

Acute Tox.4: Acute Toxicity Category 4 Asp

Tox.1: Aspiration Toxicity Category 1 Eye Irrit.2:

Eye Irritation Category 2

Flam. Lig. 2 or 3 or 4: Flammable Liquid Category 2 or 3 or 4

Skin Corr./Irrit.1 or 2 or 3: Skin Corrosion/Irritation Category 1 or 2 or 3 STOT

SE3: Specific Target Organ Toxicity Single Exposure Category 3

Sources of key data used to compile the Safety Data Sheet:

International Agency for Research on Cancer

International Air Transport Association: Dangerous Goods Regulations. International

Maritime Organization: International Maritime Dangerous Goods Code Components

supplier data

Globally harmonized system of classification and labeling of chemicals (GHS Rev.5th e.2013)

European Chemicals Agency website

EU Registration, Evaluation and Restriction of Chemicals regulation (REACH): Classification and Labeling Inventory

US California Proposition 65

US Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA) US

Department of Health & Human Services. National Toxicology Program

US Department of Transport DOT 49 CFR

US National Fire Protection Association (NFPA) 704

US National Institute for Occupational Safety & Health (NIOSH) (exposure limits)

US Occupational Safety & Health Administration (OSHA) 29 CFR 1910.1200 (Hazard Communication Standard)

US OSHA 29 CFR 1910.1000 - Table Z1 (exposure limits)

US Superfund Amendments and Reauthorization Act (SARA) Title III Sections 302; 311/312; 313 US

Toxic Substances Control Act (TSCA)

Key or legend to abbreviations and acronyms used in the safety data sheet:

ACGIH - American Conference of Governmental Industrial Hygienists CAS No

- Chemical Abstract System No.

CERCLA- US Comprehensive Environmental Response, Compensation, and Liability Act COC -

Cleveland Open Cup (flash and fire point)

DOT -Department Of Transportation EPA -

Environmental Protection Agency

IARC - International Agency for Research on Cancer IATA -

International Air Transport Association

IMDG - International Maritime Dangerous Goods code mg/

m³ - milligrams per cubic meter

mg/l - milligrams per liter

NIOSH - National Institute for Occupational Safety and Health

NFPA- US National Fire Protection Association

SDS No: 7013-1

Version: 1.1 (REG_29 CFR 1910.1200 /REG_GHS Rev.5th e.2013)

Date of last Revision: 08/19/2014

NTP - National Toxicology Program

OSHA - Occupational Safety and Health Administration

OEL-Occupational Exposure Limits

PEL - Permissible Exposure Limits ppb

- Parts Per Billion

ppm - Parts Per Million

PMCC - Pensky-Martin Closed Cup (flash point)

RCRA - EPA Resource Conservation and Recovery Act

SARA - Superfund Amendments and Reauthorization Act Title I, II, III

SDS - Safety Data Sheet

STEL- Short Term Exposure Limit TCC -

Tag Closed Cup (flash point) TLV -

Threshold Limit Value

TWA - Time Weighted Average Exposure

< - Less than

> - More than

Procedure used to derive the classification for mixtures according to Regulations 29 CFR 1900.1200 and GHS Rev.5th e.2013:

Calculation method: Classification of mixtures based on ingredients of the mixture.

LEGAL DISCLAIMER:

The information contained in this document is based upon data believed to be reliable at the time of preparing this SDS and relates only to the matters specifically mentioned in this document.

Although J.B.Chemical Co. has used reasonable skill and care in the preparation of this information, in the absence of any overriding obligations arising under a specific contract, no representation, warranty (express or implied), or guarantee is made as to the suitability, accuracy, reliability or completeness of the information; nothing in this document shall reduce the user's responsibility to satisfy itself as to the suitability, accuracy, reliability, and completeness of such information for its particular use; there is no warranty against intellectual property infringement; and J.B.Chemical Co. shall not be liable for any loss, damage or injury that may occur from the use of this information. No statement shall be construed as an endorsement of any product or process. For greater certainty, before use of information contained in this document, particularly if the product is used for a purpose or under conditions which are abnormal or not reasonably foreseeable, this information must be reviewed with the supplier of such information. J.B.Chemical Co. also dose not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product.

Prepared by: J.B.Chemical Regulatory Affairs

Revision Date: August 19, 2014

Preparation date: August 19, 2014