

# Safety Data Sheet

acc. to OSHA HCS

Printing date 05/07/2019

Reviewed on 05/07/2019

## 1 Identification

- **Product identifier**
- **Trade name:** SYNERGY TRIM COATING
- **Article number:** S-3
- **Application of the substance / the mixture** Coating
- **Details of the supplier of the safety data sheet**

- 
- **Manufacturer/Supplier:**  
BAF Industries  
8010 Dixie Highway  
Florence, KY 41042 USA  
Phone: 859-372-5900
  - **Information department:** [msds\\_info@prowax.com](mailto:msds_info@prowax.com)
  - **Emergency Telephone Number:**  
ChemTrec: 800-424-9300  
Outside USA 703-527-3887

## 2 Hazard(s) identification

- **Classification of the substance or mixture**



Flame

Highly flammable liquid and vapor.



Health hazard

Suspected of damaging fertility or the unborn child.  
Causes damage to the central nervous system through prolonged or repeated exposure.  
May be fatal if swallowed and enters airways.



Causes serious eye irritation.

- 
- **Label elements**
  - **GHS label elements**  
The product is classified and labeled according to the Globally Harmonized System (GHS).
  - **Hazard pictograms**



GHS02



GHS07



GHS08

- **Signal word** Danger
- **Hazard-determining components of labeling:**  
Distillates (petroleum), hydrotreated light  
Stoddard solvent  
cumene  
ethylbenzene
- **Hazard statements**  
Highly flammable liquid and vapor.  
Causes serious eye irritation.

(Contd. on page 2)

USA

# Safety Data Sheet

acc. to OSHA HCS

Printing date 05/07/2019

Reviewed on 05/07/2019

**Trade name: SYNERGY TRIM COATING**

(Contd. of page 1)

*Suspected of damaging fertility or the unborn child.*

*Causes damage to the central nervous system through prolonged or repeated exposure.*

*May be fatal if swallowed and enters airways.*

**· Precautionary statements**

*Obtain special instructions before use.*

*Do not handle until all safety precautions have been read and understood.*

*Keep away from heat/sparks/open flames/hot surfaces. - No smoking.*

*Keep container tightly closed.*

*Ground/bond container and receiving equipment.*

*Use explosion-proof electrical/ventilating/lighting/equipment.*

*Use only non-sparking tools.*

*Take precautionary measures against static discharge.*

*Do not breathe dust/fume/gas/mist/vapors/spray.*

*Wash thoroughly after handling.*

*Do not eat, drink or smoke when using this product.*

*Wear protective gloves/protective clothing/eye protection/face protection.*

*If swallowed: Immediately call a poison center/doctor.*

*Do NOT induce vomiting.*

*If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.*

*If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.*

*Continue rinsing.*

*IF exposed or concerned: Get medical advice/attention.*

*Get medical advice/attention if you feel unwell.*

*If eye irritation persists: Get medical advice/attention.*

*In case of fire: Use for extinction: CO<sub>2</sub>, powder or water spray.*

*Store in a well-ventilated place. Keep cool.*

*Store locked up.*

*Dispose of contents/container in accordance with local/regional/national/international regulations.*

**· Other hazards**

**· Results of PBT and vPvB assessment**

**· PBT:** Not applicable.

**· vPvB:** Not applicable.

### 3 Composition/information on ingredients

**· Chemical characterization: Mixtures**

**· Description:** Mixture of the substances listed below with nonhazardous additions.

**· Dangerous components:**

64742-47-8	Distillates (petroleum), hydrotreated light	25-50%
67-63-0	propan-2-ol	10-25%
8052-41-3	Stoddard solvent	2.5-10%
541-02-6	decamethylcyclopentasiloxane	≤2.5%
556-67-2	octamethylcyclotetrasiloxane	≤2.5%

### 4 First-aid measures

**· Description of first aid measures**

**· General information:**

*Immediately remove any clothing soiled by the product.*

*Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.*

**· After inhalation:** Supply fresh air; consult doctor in case of complaints.

**· After skin contact:** Immediately rinse with water.

**· After eye contact:**

*Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.*

(Contd. on page 3)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 05/07/2019

Reviewed on 05/07/2019

**Trade name: SYNERGY TRIM COATING**

(Contd. of page 2)

- **After swallowing:** *If symptoms persist consult doctor.*
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed** *No further relevant information available.*
- **Indication of any immediate medical attention and special treatment needed**  
*No further relevant information available.*

## \* 5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**  
*CO<sub>2</sub>, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.*
- **For safety reasons unsuitable extinguishing agents:** *Water with full jet*
- **Special hazards arising from the substance or mixture**  
*During heating or in case of fire poisonous gases are produced.*
- **Advice for firefighters**
- **Protective equipment:** *Mouth respiratory protective device.*

## \* 6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**  
*Mount respiratory protective device.  
Wear protective equipment. Keep unprotected persons away.*
- **Environmental precautions:** *Do not allow to enter sewers/ surface or ground water.*
- **Methods and material for containment and cleaning up:**  
*Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
Dispose contaminated material as waste according to item 13.  
Ensure adequate ventilation.*
- **Reference to other sections**  
*See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.*

## \* 7 Handling and storage

- **Handling:**
- **Precautions for safe handling**  
*Ensure good ventilation/exhaustion at the workplace.  
Open and handle receptacle with care.  
Prevent formation of aerosols.*
- **Information about protection against explosions and fires:**  
*Keep ignition sources away - Do not smoke.  
Protect against electrostatic charges.  
Keep respiratory protective device available.*
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** *Store in a cool location.*
- **Information about storage in one common storage facility:** *Not required.*
- **Further information about storage conditions:**  
*Keep receptacle tightly sealed.  
Store in cool, dry conditions in well sealed receptacles.*
- **Specific end use(s)** *No further relevant information available.*

USA

(Contd. on page 4)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 05/07/2019

Reviewed on 05/07/2019

Trade name: SYNERGY TRIM COATING

(Contd. of page 3)

## 8 Exposure controls/personal protection

· **Additional information about design of technical systems:** No further data; see item 7.

· **Control parameters**

· **Components with limit values that require monitoring at the workplace:**

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the other constituents have no known exposure limits.

### 67-63-0 propan-2-ol

PEL	Long-term value: 980 mg/m <sup>3</sup> , 400 ppm
REL	Short-term value: 1225 mg/m <sup>3</sup> , 500 ppm Long-term value: 980 mg/m <sup>3</sup> , 400 ppm
TLV	Short-term value: 984 mg/m <sup>3</sup> , 400 ppm Long-term value: 492 mg/m <sup>3</sup> , 200 ppm BEI

### 8052-41-3 Stoddard solvent

PEL	Long-term value: 2900 mg/m <sup>3</sup> , 500 ppm
REL	Long-term value: 350 mg/m <sup>3</sup> Ceiling limit value: 1800* mg/m <sup>3</sup> *15-min
TLV	Long-term value: 525 mg/m <sup>3</sup> , 100 ppm

### 556-67-2 octamethylcyclotetrasiloxane

WEEL	Long-term value: 10* ppm *OARS WEEL
------	--

· **Ingredients with biological limit values:**

### 67-63-0 propan-2-ol

BEI	40 mg/L Medium: urine Time: end of shift at end of workweek Parameter: Acetone (background, nonspecific)
-----	---

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

· **Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

(Contd. on page 5)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 05/07/2019

Reviewed on 05/07/2019

**Trade name: SYNERGY TRIM COATING**

(Contd. of page 4)

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles

## 9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

· <b>Form:</b>	Liquid
· <b>Color:</b>	Colorless
· <b>Odor:</b>	Alcohol-like
· <b>Odor threshold:</b>	Not determined.

· **pH-value:** Not applicable

· **Change in condition**

· <b>Melting point/Melting range:</b>	Undetermined.
· <b>Boiling point/Boiling range:</b>	65 °C (149 °F)

· **Flash point:** 12 °C (53.6 °F)

· **Flammability (solid, gaseous):** Not applicable.

· **Ignition temperature:** 459 °C (858.2 °F)

· **Decomposition temperature:** Not determined.

· **Auto igniting:** Product is not selfigniting.

· **Danger of explosion:** Product is not explosive. However, formation of explosive air/vapor mixtures are possible.

· **Explosion limits:**

· <b>Lower:</b>	2 Vol %
· <b>Upper:</b>	12 Vol %

· **Vapor pressure at 20 °C (68 °F):** 43 hPa (32.3 mm Hg)

· **Density at 20 °C (68 °F):** 0.8148 g/cm<sup>3</sup> (6.7995 lbs/gal)

· **Relative density** Not determined.

· **Vapor density** Not determined.

· **Evaporation rate** Not determined.

· **Solubility in / Miscibility with**

· **Water:** Not miscible or difficult to mix.

· **Partition coefficient (n-octanol/water):** Not determined.

· **Viscosity:**

· <b>Dynamic:</b>	Not determined
· <b>Kinematic at 40 °C (104 °F):</b>	<20.5 mm <sup>2</sup> /s

(Contd. on page 6)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 05/07/2019

Reviewed on 05/07/2019

**Trade name: SYNERGY TRIM COATING**

(Contd. of page 5)

· <b>Solvent content:</b>	
<b>Organic solvents:</b>	71.0 %
<b>VOC content:</b>	26.00 %
	211.9 g/l / 1.77 lb/gal
· <b>Solids content:</b> 0.0 %	
· <b>Other information</b> No further relevant information available.	

## 10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

## 11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**
- **Primary irritant effect:**
- **on the skin:** No irritant effect.
- **on the eye:** Irritating effect.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**  
The product shows the following dangers according to internally approved calculation methods for preparations:  
Irritant
- **Carcinogenic categories**

### · IARC (International Agency for Research on Cancer)

67-63-0	propan-2-ol	3
98-82-8	cumene	2B
100-41-4	ethylbenzene	2B

### · NTP (National Toxicology Program)

98-82-8	cumene	R
---------	--------	---

### · OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

## 12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**  
Water hazard class 1 (Self-assessment); slightly hazardous for water

(Contd. on page 7)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 05/07/2019

Reviewed on 05/07/2019

**Trade name: SYNERGY TRIM COATING**

(Contd. of page 6)



Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

## 13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**  
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

## 14 Transport information

- **UN-Number**
- **DOT, ADR, IMDG, IATA** UN1219
- **UN proper shipping name**
- **DOT** Isopropanol
- **ADR** 1219 ISOPROPANOL (ISOPROPYL ALCOHOL)
- **IMDG, IATA** ISOPROPANOL (ISOPROPYL ALCOHOL)
- **Transport hazard class(es)**
- **DOT**
- 
- **Class** 3 Flammable liquids
- **Label** 3
- **ADR, IMDG, IATA**
- 
- **Class** 3 Flammable liquids
- **Label** 3
- **Packing group**
- **DOT, ADR, IMDG, IATA** II
- **Environmental hazards:** Not applicable.
- **Special precautions for user** Warning: Flammable liquids
- **Danger code (Kemler):** 33
- **EMS Number:** F-E,S-D
- **Stowage Category** B
- **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code** Not applicable.

(Contd. on page 8)

USA

# Safety Data Sheet

acc. to OSHA HCS

Printing date 05/07/2019

Reviewed on 05/07/2019

Trade name: SYNERGY TRIM COATING

(Contd. of page 7)

· **Transport/Additional information:**

· **DOT**

· **Quantity limitations**

On passenger aircraft/rail: 5 L

On cargo aircraft only: 60 L

· **ADR**

· **Excepted quantities (EQ)**

Code: E2

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 500 ml

· **IMDG**

· **Limited quantities (LQ)**

1L

· **Excepted quantities (EQ)**

Code: E2

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 500 ml

· **UN "Model Regulation":**

UN 1219 ISOPROPANOL (ISOPROPYL ALCOHOL), 3, II

## 15 Regulatory information

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**

· **Sara**

· **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

· **Section 313 (Specific toxic chemical listings):**

67-63-0 propan-2-ol

67-56-1 methanol

98-82-8 cumene

100-41-4 ethylbenzene

· **TSCA (Toxic Substances Control Act) All ingredients are listed**

· **TSCA new (21st Century Act): (Substances not listed)**

8052-41-3 Stoddard solvent

· **Hazardous Air Pollutants**

67-56-1 methanol

98-82-8 cumene

100-41-4 ethylbenzene

· **Proposition 65**

· **Chemicals known to cause cancer:**

98-82-8 cumene

100-41-4 ethylbenzene

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

67-56-1 methanol

· **Carcinogenic categories**

· **EPA (Environmental Protection Agency)**

98-82-8 cumene

D, CBD

(Contd. on page 9)

USA



# Safety Data Sheet

acc. to OSHA HCS

Printing date 05/07/2019

Reviewed on 05/07/2019

**Trade name: SYNERGY TRIM COATING**

(Contd. of page 8)

100-41-4	ethylbenzene	D
· <b>TLV (Threshold Limit Value established by ACGIH)</b>		
67-63-0	propan-2-ol	A4
100-41-4	ethylbenzene	A3

· <b>NIOSH-Ca (National Institute for Occupational Safety and Health)</b>		
None of the ingredients is listed.		

· **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**



GHS02    GHS07    GHS08

· **Signal word** *Danger*

· **Hazard-determining components of labeling:**

*Distillates (petroleum), hydrotreated light  
Stoddard solvent  
cumene  
ethylbenzene*

· **Hazard statements**

*Highly flammable liquid and vapor.  
Causes serious eye irritation.  
Suspected of damaging fertility or the unborn child.  
Causes damage to the central nervous system through prolonged or repeated exposure.  
May be fatal if swallowed and enters airways.*

· **Precautionary statements**

*Obtain special instructions before use.  
Do not handle until all safety precautions have been read and understood.  
Keep away from heat/sparks/open flames/hot surfaces. - No smoking.  
Keep container tightly closed.  
Ground/bond container and receiving equipment.  
Use explosion-proof electrical/ventilating/lighting/equipment.  
Use only non-sparking tools.  
Take precautionary measures against static discharge.  
Do not breathe dust/fume/gas/mist/vapors/spray.  
Wash thoroughly after handling.  
Do not eat, drink or smoke when using this product.  
Wear protective gloves/protective clothing/eye protection/face protection.  
If swallowed: Immediately call a poison center/doctor.  
Do NOT induce vomiting.  
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.  
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.  
Continue rinsing.  
If exposed or concerned: Get medical advice/attention.  
Get medical advice/attention if you feel unwell.  
If eye irritation persists: Get medical advice/attention.  
In case of fire: Use for extinction: CO<sub>2</sub>, powder or water spray.  
Store in a well-ventilated place. Keep cool.*

*Store locked up.*

*Dispose of contents/container in accordance with local/regional/national/international regulations.*

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

USA

(Contd. on page 10)

# Safety Data Sheet

## acc. to OSHA HCS

Printing date 05/07/2019

Reviewed on 05/07/2019

**Trade name: SYNERGY TRIM COATING**

(Contd. of page 9)

### 16 Other information

*This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.*

· **Date of preparation / last revision** 05/07/2019 / 5

· **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

Flam. Liq. 2: Flammable liquids – Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A

Repr. 2: Reproductive toxicity – Category 2

STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1

Asp. Tox. 1: Aspiration hazard – Category 1

· **\* Data compared to the previous version altered.**

USA