

SAFETY DATA SHEET



Car Brite™ SELECT TIRE & TRIM DRESSING

Version 5.0 Revision Date: 09/06/2018 SDS Number: 600000000195 Date of last issue: 08/27/2018
Date of first issue: 05/23/2016

SECTION 1. IDENTIFICATION

Product name : CB SELECT TIRE & TRIM DRSG 4/1 GA
Product code : 593712

Manufacturer or supplier's details

Company name of supplier : Niteo Products, LLC
Address : Dallas TX 75225
Email Address : EHS@niteoproducts.com
Telephone : 1-844-696-4836
Emergency telephone number : 1-800-424-9300 / 1-703-741-5970

Recommended use of the chemical and restrictions on use

Recommended use : TIRE SHINE / DRESSING
Restrictions on use : Use only outdoors or in a well-ventilated area.

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with 29 CFR 1910.1200

Flammable liquids : Category 4
Reproductive toxicity : Category 2
Specific target organ toxicity - single exposure : Category 3 (Central nervous system)

GHS label elements

Hazard pictograms :

Signal word : Warning

Hazard statements : Combustible liquid.
May cause drowsiness or dizziness.
Suspected of damaging fertility or the unborn child.

Precautionary statements : **Prevention:**
Obtain special instructions before use.

Car Brite™ SELECT TIRE & TRIM DRESSING

Version 5.0 Revision Date: 09/06/2018 SDS Number: 600000000195 Date of last issue: 08/27/2018
Date of first issue: 05/23/2016

Do not handle until all safety precautions have been read and understood.
Keep away from heat/sparks/open flames/hot surfaces. No smoking.
Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.
Use only outdoors or in a well-ventilated area.
Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response:

IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.
IF exposed or concerned: Get medical advice/ attention.
In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Storage:

Store in a well-ventilated place. Keep container tightly closed.
Store in a well-ventilated place. Keep cool.
Store locked up.

Disposal:

Dispose of contents/ container to an approved waste disposal plant.

Other hazards

Static-accumulating flammable liquid.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

Chemical name	CAS-No.	Concentration (% w/w)
Distillates (petroleum)	64742-47-8	>= 50 - < 70
Naphtha (petroleum)	64742-49-0	>= 1 - < 5

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

SECTION 4. FIRST AID MEASURES

General advice : Move out of dangerous area.
Show this safety data sheet to the doctor in attendance.
Do not leave the victim unattended.

If inhaled : Move to fresh air.
Consult a physician after significant exposure.
If unconscious, place in recovery position and seek medical advice.
If symptoms persist, call a physician.

In case of skin contact : If on clothes, remove clothes.
Remove contaminated clothing. If irritation develops, get medical attention.
If on skin, rinse well with water.

SAFETY DATA SHEET



Car Brite™ SELECT TIRE & TRIM DRESSING

Version 5.0 Revision Date: 09/06/2018 SDS Number: 600000000195 Date of last issue: 08/27/2018
Date of first issue: 05/23/2016

- Wash contaminated clothing before re-use.
If skin irritation persists, call a physician.
- In case of eye contact : Flush eyes with water as a precaution.
Remove contact lenses.
Protect unharmed eye.
Keep eye wide open while rinsing.
- If swallowed : Obtain medical attention.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.
- Most important symptoms and effects, both acute and delayed : May cause drowsiness or dizziness.
Suspected of damaging fertility or the unborn child.
-

SECTION 5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Water spray
Carbon dioxide (CO2)
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during fire-fighting : If product is heated above its flash point it will produce vapors sufficient to support combustion. Vapors are heavier than air and may travel along the ground and be ignited by heat, pilot lights, other flames and ignition sources at locations near the point of release.
Do not allow run-off from fire fighting to enter drains or water courses.
- Hazardous combustion products : Carbon oxides
Silicon oxides
- Specific extinguishing methods : Product is compatible with standard fire-fighting agents.
- Further information : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
Use a water spray to cool fully closed containers.
- Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.
-

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
Remove all sources of ignition.
Avoid breathing dust.
Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.
-

Car Brite™ SELECT TIRE & TRIM DRESSING

Version 5.0 Revision Date: 09/06/2018 SDS Number: 600000000195 Date of last issue: 08/27/2018
Date of first issue: 05/23/2016

- Environmental precautions : Prevent further leakage or spillage if safe to do so.
Prevent product from entering drains.
Do not flush into surface water or sanitary sewer system.
If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods and materials for containment and cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).
Keep in suitable, closed containers for disposal.

SECTION 7. HANDLING AND STORAGE

- Advice on protection against fire and explosion : Electrically bond and ground all containers, personnel and equipment before transfer or use of material. Special precautions may be necessary to dissipate static electricity for non-conductive containers. Use proper bonding and grounding during product transfer as described in National Fire Protection Association document NFPA 77.
Keep away from open flames, hot surfaces and sources of ignition.
Do not spray on a naked flame or any incandescent material.
- Advice on safe handling : Avoid formation of aerosol.
Provide sufficient air exchange and/or exhaust in work rooms.
Do not breathe vapours/dust.
Do not smoke.
Avoid contact with skin and eyes.
Dispose of rinse water in accordance with local and national regulations.
Container hazardous when empty.
Smoking, eating and drinking should be prohibited in the application area.
For personal protection see section 8.
- Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated place.
Containers which are opened must be carefully resealed and kept upright to prevent leakage.
Observe label precautions.
No smoking.
- Further information on storage stability : No decomposition if stored and applied as directed.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Distillates (petroleum)	64742-47-8	TWA (Mist)	5 mg/m ³	OSHA Z-1

SAFETY DATA SHEET



Car Brite™ SELECT TIRE & TRIM DRESSING

Version 5.0 Revision Date: 09/06/2018 SDS Number: 600000000195 Date of last issue: 08/27/2018
Date of first issue: 05/23/2016

		TWA	200 mg/m3 (total hydrocarbon vapor)	ACGIH
		TWA (Mist)	5 mg/m3	OSHA P0
		TWA (Mist)	5 mg/m3	NIOSH REL
		ST (Mist)	10 mg/m3	NIOSH REL
Naphtha (petroleum)	64742-49-0	TWA	500 ppm 2,000 mg/m3	OSHA Z-1
		TWA	400 ppm 1,600 mg/m3	OSHA P0

Engineering measures : Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

Personal protective equipment

Respiratory protection : In the case of vapour formation use a respirator with an approved filter.

Hand protection

Remarks : Wear resistant gloves (consult your safety equipment supplier). The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye protection : Not required under normal conditions of use. Wear splash-proof safety goggles if material could be misted or splashed into eyes.

Skin and body protection : Choose body protection according to the amount and concentration of the dangerous substance at the work place.
Wear as appropriate:
Impervious clothing
Safety shoes

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice.
When using do not smoke.
When using do not eat or drink.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid
Colour : purple
Odour : sweet
pH : No data available
Melting point/freezing point : No data available
Boiling point/boiling range : 65 °C
(1,013 hPa)

SAFETY DATA SHEET



Car Brite™ SELECT TIRE & TRIM DRESSING

Version 5.0 Revision Date: 09/06/2018 SDS Number: 600000000195 Date of last issue: 08/27/2018
Date of first issue: 05/23/2016

Flash point : The value is calculated
: 70 °C
Method: Tag closed cup

Evaporation rate : No data available

Flammability (solid, gas) : No data available

Flammability (liquids) : Static-accumulating flammable liquid.

Self-ignition : No data available

Upper explosion limit / Upper flammability limit : 8 %(V)
The value is calculated

Lower explosion limit / Lower flammability limit : 0.7 %(V)
The value is calculated

Vapour pressure : 16 hPa (20 °C)
The value is calculated

Density : 0.8594 g/cm³

Solubility(ies)
Water solubility : No data available

Partition coefficient: n-octanol/water : No data available

Viscosity
Viscosity, dynamic : No data available
Viscosity, kinematic : 30.9 mm²/s (40 °C)

Oxidizing properties : No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No dangerous reaction known under conditions of normal use.
No decomposition if stored and applied as directed.

Chemical stability : Stable under normal conditions.
No decomposition if stored and applied as directed.

Possibility of hazardous reactions : No decomposition if stored and applied as directed.
Vapours may form explosive mixture with air.

Conditions to avoid : Heat, flames and sparks.

Incompatible materials : Strong oxidizing agents
Strong reducing agents

Hazardous decomposition products : Carbon oxides
Silicon oxides

SAFETY DATA SHEET



Car Brite™ SELECT TIRE & TRIM DRESSING

Version 5.0 Revision Date: 09/06/2018 SDS Number: 600000000195 Date of last issue: 08/27/2018
Date of first issue: 05/23/2016

OSHA No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

Reproductive toxicity

Suspected of damaging fertility or the unborn child.

Components:

Naphtha (petroleum):

Reproductive toxicity - Assessment : Some evidence of adverse effects on sexual function and fertility, and/or on development, based on animal experiments.

STOT - single exposure

May cause drowsiness or dizziness.

Components:

Distillates (petroleum):

Target Organs: Central nervous system
Assessment: May cause drowsiness or dizziness.

Naphtha (petroleum):

Exposure routes: Inhalation
Target Organs: Central nervous system
Assessment: May cause drowsiness or dizziness.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

Product:

No aspiration toxicity classification

Components:

Distillates (petroleum):

May be fatal if swallowed and enters airways.

Naphtha (petroleum):

May be fatal if swallowed and enters airways.

Further information

Product:

Remarks: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.

SAFETY DATA SHEET



Car Brite™ SELECT TIRE & TRIM DRESSING

Version 5.0 Revision Date: 09/06/2018 SDS Number: 600000000195 Date of last issue: 08/27/2018
Date of first issue: 05/23/2016

SECTION 12. ECOLOGICAL INFORMATION

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

- Waste from residues : Dispose of in accordance with all applicable local, state and federal regulations.
- Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.
Do not burn, or use a cutting torch on, the empty drum.

SECTION 14. TRANSPORT INFORMATION

Dangerous goods descriptions (if indicated below) may not reflect quantity, end-use, or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

International Regulations

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations

49 CFR

Not regulated as a dangerous good

49 CFR

Not regulated as a dangerous good

SECTION 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know Act

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
Toluene	108-88-3	100	100 (F005)
Benzene	71-43-2	10	10 (D018)
Benzene	71-43-2	10	*
Ethylbenzene	100-41-4	100	100 (F003)*

*: Calculated RQ exceeds reasonably attainable upper limit.

SAFETY DATA SHEET



Car Brite™ SELECT TIRE & TRIM DRESSING

Version 5.0 Revision Date: 09/06/2018 SDS Number: 600000000195 Date of last issue: 08/27/2018
Date of first issue: 05/23/2016

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : Flammable (gases, aerosols, liquids, or solids)
Hazard not otherwise classified (physical hazards)
Specific target organ toxicity (single or repeated exposure)
Reproductive toxicity

SARA 313 : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.


California Prop. 65

WARNING: This product can expose you to chemicals including Naphthalene, Ethylbenzene, Benzene, which is/are known to the State of California to cause cancer, and Toluene, Benzene, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

SECTION 16. OTHER INFORMATION

Further information

NFPA:



Revision Date : 09/06/2018

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

SAFETY DATA SHEET



Car Brite™ SELECT TIRE & TRIM DRESSING

Version	Revision Date:	SDS Number:	Date of last issue: 08/27/2018
5.0	09/06/2018	600000000195	Date of first issue: 05/23/2016

US / EN