



Version 3.0	Revision Date: 09/13/2018		DS Number: 0000000824	Date of last issue: 09/06/2018 Date of first issue: 05/23/2016			
SECTION	SECTION 1. IDENTIFICATION						
Prod	Product name		EASIOFF YELLC	W PASTE WX 12/16 OC			
Prod	luct code	:	CBOOA010-01				
	ufacturer or supplier's						
Com	pany name of supplier	:	Niteo Products, L	LC			
Addı	Address		Dallas TX 75225				
Ema	Email Address		EHS@niteoproducts.com				
Tele	Telephone		1-844-696-4836				
Eme ber	Emergency telephone num- ber		1-800-424-9300 /	/ 1-703-741-5970			
Recommended use of the chemical and restrictions on use				ons on use			
Reco	ommended use	:	WAX				
Rest	rictions on use	:	Use only outdoor	s or in a well-ventilated area.			

## SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accorda Skin irritation	GHS classification in accordance with 29 CFR 1910.1200Skin irritation: Category 2				
Specific target organ toxicity - single exposure	:	Category 3 (Central nervous system)			
GHS label elements Hazard pictograms	:	<u>!</u>			
Signal word	:	Warning			
Hazard statements	:	Causes skin irritation. May cause drowsiness or dizziness.			
Precautionary statements	:	<b>Prevention:</b> Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray. Wash skin thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves.			



Version	Revision Date:	SDS Number:	Date of last issue: 09/06/2018
3.0	09/13/2018	60000000824	Date of first issue: 05/23/2016

#### Response:

IF ON SKIN: Wash with plenty of soap and water. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell. If skin irritation occurs: Get medical advice/ attention. Take off contaminated clothing and wash before reuse.

#### Storage:

Store in a well-ventilated place. Keep container tightly closed. Store locked up.

#### Disposal:

Dispose of contents/ container to an approved waste disposal plant.

#### Other hazards

None known.

## SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

#### Hazardous components

Chemical name	CAS-No.	Concentration (% w/w)
Solvent naphtha (petroleum)	64742-88-7	>= 0 - <= 80
Raffinates (petroleum), sorption process	64741-85-1	>= 0 - <= 80

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

#### **SECTION 4. FIRST AID MEASURES**

General advice :	Move out of dangerous area. Show this safety data sheet to the doctor in attendance. Do not leave the victim unattended.
If inhaled :	Move to fresh air. Consult a physician after significant exposure. If unconscious, place in recovery position and seek medical advice. If symptoms persist, call a physician.
In case of skin contact :	If on clothes, remove clothes. Seek medical advice. Remove contaminated clothing. If irritation develops, get med- ical attention. If on skin, rinse well with water. Wash contaminated clothing before re-use. If skin irritation persists, call a physician.
In case of eye contact :	Flush eyes with water as a precaution. Remove contact lenses. Protect unharmed eye. Keep eye wide open while rinsing.



Vers 3.0	sion	Revision Date: 09/13/2018		0S Number: 0000000824	Date of last issue: 09/06/2018 Date of first issue: 05/23/2016
If swallowed		:	Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician.		
	Most important symptoms and effects, both acute and delayed		:	Causes skin irritation. May cause drowsiness or dizziness.	
SEC	CTION 5	. FIREFIGHTING MEA	SU	RES	
	Suitabl	e extinguishing media	:	Water spray	
	Unsuita media	able extinguishing	:	High volume wate	r jet
	Specific hazards during fire- fighting		:	sufficient to support and may travel and lights, other flame point of release.	ed above its flash point it will produce vapors ort combustion. Vapors are heavier than air ong the ground and be ignited by heat, pilot s and ignition sources at locations near the off from fire fighting to enter drains or water
	Hazard ucts	lous combustion prod-	:	Carbon oxides Silicon oxides	
	Specifi ods	c extinguishing meth-	:	Product is compa	tible with standard fire-fighting agents.
	Further	rinformation	:	cumstances and t Fire residues and	measures that are appropriate to local cir- he surrounding environment. contaminated fire extinguishing water must accordance with local regulations.
	Specia for firef	l protective equipment ïghters	:	In the event of fire	e, wear self-contained breathing apparatus.

## SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protec- tive equipment and emer- gency procedures	:	Use personal protective equipment. Avoid dust formation. Avoid breathing dust. Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.
Environmental precautions	:	Prevent further leakage or spillage if safe to do so. Prevent product from entering drains. Do not flush into surface water or sanitary sewer system. If the product contaminates rivers and lakes or drains inform respective authorities.
Methods and materials for containment and cleaning up	:	Keep in suitable, closed containers for disposal.



Version 3.0	Revision Date: 09/13/2018	SDS Number: 60000000824	Date of last issue: 09/06/2018 Date of first issue: 05/23/2016				
SECTIC	SECTION 7. HANDLING AND STORAGE						
Advice on protection against fire and explosion		Avoid dust form	to prevent the build up of electrostatic charge. ation. riate exhaust ventilation at places where dust				
Advice on safe handling		Do not breathe Do not smoke. Avoid contact w Dispose of rinse regulations. Container haza Smoking, eating plication area.	nt air exchange and/or exhaust in work rooms.				
Co	nditions for safe storage	<ul> <li>Keep container tightly closed in a dry and well-ventilat place.</li> <li>Containers which are opened must be carefully resear kept upright to prevent leakage.</li> <li>Observe label precautions.</li> </ul>					
	ther information on stor- e stability	: No decompositi	on if stored and applied as directed.				

## SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parame- ters / Permissible concentration	Basis
Solvent naphtha (petroleum)	64742-88-7	TWA	200 mg/m3 (total hydrocarbon vapor)	ACGIH

#### Hazardous components without workplace control parameters

Components	CAS-No.	
Raffinates (petroleum), sorp-	64741-85-1	
tion process		
Engineering measures :	ventilation to r applicable) or apparent adve	ent mechanical (general and/or local exhaust) naintain exposure below exposure guidelines (if below levels that cause known, suspected or erse effects. priate exhaust ventilation at places where dust

#### Personal protective equipment

Respiratory protection	
------------------------	--

: In the case of dust or aerosol formation use respirator with an approved filter.



Version 3.0	Revision Date: 09/13/2018	SDS Number: 60000000824	Date of last issue: 09/06/2018 Date of first issue: 05/23/2016	
Hand	protection			
Remarks		: Wear resistant gloves (consult your safety equipment suppli- er). The suitability for a specific workplace should be dis- cussed with the producers of the protective gloves. Discard gloves that show tears, pinholes, or signs of wear.		
Eye protection		: Safety glasse	S	
Skin and body protection		centration of	<ul> <li>Choose body protection according to the amount and con- centration of the dangerous substance at the work place.</li> <li>Wear as appropriate: Safety shoes</li> </ul>	
Hygie	ene measures	practice. Avoid breathi When using c	•	

## SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	:	paste
Colour	:	yellow
Odour	:	pleasant
рН	:	No data available
Melting point/freezing point	:	No data available
Boiling point/boiling range	:	35 °C (1,013 hPa)
Flash point	:	The value is calculated
Evaporation rate	:	No data available
Flammability (solid, gas)	:	No data available
Self-ignition	:	No data available
Upper explosion limit / Upper flammability limit	:	7 %(V) The value is calculated
Lower explosion limit / Lower flammability limit	:	0.7 %(V) The value is calculated
Vapour pressure	:	6.67 hPa (20 °C) The value is calculated
Density	:	0.871 g/cm3
Solubility(ies)		



Version 3.0	Revision Date: 09/13/2018	SDS Number: 60000000824	Date of last issue: 09/06/2018 Date of first issue: 05/23/2016	
W	ater solubility	: insoluble		
	ion coefficient: n- ol/water	: No data avail	able	
Visco Vis	sity scosity, dynamic	: No data avail	able	
Vi	scosity, kinematic	: No data avail	able	
Oxidi	zing properties	: No data avail	able	

## SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	No decomposition if stored and applied as directed.
Chemical stability	:	No decomposition if stored and applied as directed.
Possibility of hazardous reac- tions	:	No decomposition if stored and applied as directed. Hazardous polymerisation does not occur.
Conditions to avoid	:	No data available
Incompatible materials	:	Strong oxidizing agents
Hazardous decomposition products	:	Carbon oxides Silicon oxides

## SECTION 11. TOXICOLOGICAL INFORMATION

# Information on likely routes of exposure

Inhalation
Skin contact
Eye contact
Ingestion

## Acute toxicity

Not classified based on available information.

```
Product:
```

Acute oral toxicity	:	Acute toxicity estimate: 3,125 mg/kg Method: Calculation method
Acute dermal toxicity	:	Acute toxicity estimate: 2,778 mg/kg Method: Calculation method

## Components:

Solvent naphtha (petroleum		
Acute oral toxicity	:	LD50 (Rat): > 5,000 mg/kg
Acute inhalation toxicity	:	LC50 (Rat): > 5.28 mg/l Exposure time: 4 h Test atmosphere: vapour



sion	Revision Date: 09/13/2018	SDS Number: 60000000824	Date of last issue: 09/06/2018 Date of first issue: 05/23/2016
			D Test Guideline 403 No adverse effect has been observed in acute city tests.
Acute	e dermal toxicity		D Test Guideline 402 No adverse effect has been observed in acute
	nates (petroleum), so	orption process:	
Acute	oral toxicity	: LD50 (Rat): > 2	2,000 mg/kg
Acute	inhalation toxicity	: LC50 (Rat): > Exposure time Test atmosphe Assessment: N inhalation toxic	: 4 h ere: dust/mist No adverse effect has been observed in acute
Acute	e dermal toxicity	: LD50 (Rabbit):	> 2,000 mg/kg
Caus <u>Prod</u>	<b>corrosion/irritation</b> es skin irritation. u <u>ct:</u> arks: May cause skin i	rritation and/or dermat	iitis.
Cause Prode Rema Com Solve Speci	es skin irritation. <b>uct:</b>		iitis.
Cause Produ Rema Comp Solve Speci Resu Raffin	es skin irritation. <u>uct:</u> arks: May cause skin ir ponents: ent naphtha (petroleu ies: Rabbit	um): prption process:	
Cause Produ Rema Com Solve Speci Resu Resu	es skin irritation. uct: arks: May cause skin ir ponents: ent naphtha (petroleu les: Rabbit lt: Skin irritation nates (petroleum), sc	um): prption process:	
Cause Produ Rema Solve Speci Resu Resu Resu Resu	es skin irritation. <u>uct:</u> arks: May cause skin in <u>ponents:</u> ent naphtha (petroleu les: Rabbit It: Skin irritation nates (petroleum), so It: Repeated exposure	Im): prption process: may cause skin drynd irritation	
Cause Produ Rema Solve Speci Resu Resu Resu Resu Serio Not c Produ	es skin irritation. <u>uct:</u> arks: May cause skin in <u>ponents:</u> ent naphtha (petroleu es: Rabbit It: Skin irritation nates (petroleum), so It: Repeated exposure It: No skin irritation us eye damage/eye in lassified based on avanuation usticked based on avanuation usticked based on avanuation	Im): prption process: may cause skin drynd irritation hilable information.	
Cause Produ Rema Solve Speci Resu Resu Resu Resu Resu Resu Resu Resu	es skin irritation. <u>uct:</u> arks: May cause skin in <u>ponents:</u> ent naphtha (petroleu es: Rabbit It: Skin irritation nates (petroleum), so It: Repeated exposure It: No skin irritation us eye damage/eye in lassified based on avanuation usticked based on avanuation usticked based on avanuation	Im): prption process: may cause skin drynd irritation hilable information.	ess or cracking.
Cause Produ Rema Solve Speci Resu Resu Resu Serio Not c Produ Rema Solve	es skin irritation. <u>uct:</u> arks: May cause skin in <u>ponents:</u> ent naphtha (petroleu es: Rabbit It: Skin irritation nates (petroleum), so It: Repeated exposure It: No skin irritation us eye damage/eye in lassified based on avain uct: arks: Product dust may	Im):         orption process:         may cause skin drynd         irritation         illable information.         y be irritating to eyes, state	ess or cracking.



# R DEITA THE A CLOFE VELLOW Deate Ma

ar Brit	e™ EASI-OFF	YELLOW Past	e Wax
ersion )	Revision Date: 09/13/2018	SDS Number: 60000000824	Date of last issue: 09/06/2018 Date of first issue: 05/23/2016
Respir	atory or skin sensi	tisation	
	ensitisation ssified based on ava	ailable information.	
-	atory sensitisation		
Comp	onents:		
Test Ty Specie	<b>ht naphtha (petrolei</b> ype: Buehler Test s: Guinea pig sment: Does not cau	um): se skin sensitisation.	
Germ	cell mutagenicity		
Not cla	ssified based on ava	ailable information.	
Comp	onents:		
Solver	nt naphtha (petroleu	um):	
Genoto	oxicity in vitro		almonella typhimurium ation: with and without metabolic activation
Carcin	ogenicity		
Not cla IARC	ssified based on ava	No component of	this product present at levels greater than or dentified as probable, possible or confirmed n by IARC.
OSHA			this product present at levels greater than or n OSHA's list of regulated carcinogens.
NTP			this product present at levels greater than or dentified as a known or anticipated carcinogen
•	ductive toxicity ssified based on ava	ailable information.	
STOT	- single exposure		
May ca	ause drowsiness or c	lizziness.	

## Components:

#### Solvent naphtha (petroleum):

Exposure routes: inhalation (vapour) Target Organs: Central nervous system Assessment: The substance or mixture is classified as specific target organ toxicant, single exposure, category 3 with narcotic effects.

## Raffinates (petroleum), sorption process:

Exposure routes: Inhalation



Version	Revision Date:	SDS Number:
3.0	09/13/2018	60000000824

Date of last issue: 09/06/2018 Date of first issue: 05/23/2016

Target Organs: Central nervous system Assessment: May cause drowsiness or dizziness.

#### STOT - repeated exposure

Not classified based on available information.

#### Aspiration toxicity

Not classified based on available information.

#### Components:

#### Solvent naphtha (petroleum):

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

#### Raffinates (petroleum), sorption process:

May be fatal if swallowed and enters airways.

#### Further information

#### Product:

Remarks: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.

#### SECTION 12. ECOLOGICAL INFORMATION

#### SECTION 13. DISPOSAL CONSIDERATIONS

#### **Disposal methods**

Waste from residues	:	Dispose of in accordance with all applicable local, state and federal regulations.
Contaminated packaging	:	Empty remaining contents. Dispose of as unused product. Do not re-use empty containers.

#### **SECTION 14. TRANSPORT INFORMATION**

Dangerous goods descriptions (if indicated below) may not reflect quantity, end-use, or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

#### International Regulations

#### IATA-DGR

Not regulated as a dangerous good

#### IMDG-Code

Not regulated as a dangerous good



Version	Revision Date:	SDS Number:	Date of last issue: 09/06/2018
3.0	09/13/2018	60000000824	Date of first issue: 05/23/2016

## Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

## **National Regulations**

**49 CFR** Not regulated as a dangerous good

#### 49 CFR

Not regulated as a dangerous good

## **SECTION 15. REGULATORY INFORMATION**

#### EPCRA - Emergency Planning and Community Right-to-Know Act

#### **CERCLA Reportable Quantity**

This material does not contain any components with a CERCLA RQ.

#### SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

#### SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards	:	Skin corrosion or irritation Specific target organ toxicity (single or repeated exposure)
SARA 313	:	This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

#### California Prop. 65

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.






Version	Revision Date:	SDS Number:	Date of last issue: 09/06/2018
3.0	09/13/2018	60000000824	Date of first issue: 05/23/2016

## **SECTION 16. OTHER INFORMATION**

#### **Further information**



Revision Date : 09/13/2018

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN