Printing date 05/07/2019

Reviewed on 05/07/2019

1 Identification

- · Product identifier
- · Trade name: SYNERGY CERAMIC GLASS COATING
- Article number: S-2
- · Application of the substance / the mixture Coating

• Details of the supplier of the safety data sheet

- Manufacturer/Supplier: BAF Industries 8010 Dixie Highway Florence, KY 41042 USA Phone:859-372-5900
- Information department: msds_info@prowax.com
- Emergency Telephone Number: ChemTrec: 800-424-9300 Outside USA 703-527-3887

2 Hazard(s) identification

· Classification of the substance or mixture

Flame

Highly flammable liquid and vapor.



May be fatal if swallowed and enters airways.



Causes skin irritation. May cause drowsiness or dizziness.

- · Label elements
- · GHS label elements
- The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms



· Signal word Danger

Hazard-determining components of labeling: aliphatic hydrocarbon
Hazard statements
Highly flammable liquid and vapor. Causes skin irritation.
May cause drowsiness or dizziness.
May be fatal if swallowed and enters airways.
Precautionary statements
Keen away from heat/sparks/open flames/hot surfaces - N

Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Ground/bond container and receiving equipment.

(Contd. on page 2)

USA

Printing date 05/07/2019

Reviewed on 05/07/2019

Trade name: SYNERGY CERAMIC GLASS COATING

	(Contd. of page 1)
Use explosion-proof electrical/ventilating/lighting/equipment.	
Use only non-sparking tools.	
Take precautionary measures against static discharge.	
Avoid breathing dust/fume/gas/mist/vapors/spray	
Wash thoroughly after handling.	
Use only outdoors or in a well-ventilated area.	
Wear protective gloves/protective clothing/eye protection/face protection.	
If swallowed: Immediately call a poison center/doctor.	
Specific treatment (see on this label).	
Do NOT induce vomiting.	
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/sho	wer.
IF INHALED: Remove person to fresh air and keep comfortable for breathing.	
Call a poison center/doctor if you feel unwell.	
Take off contaminated clothing and wash it before reuse.	
If skin irritation occurs: Get medical advice/attention.	
In case of fire: Use for extinction: CO2, powder or water spray.	
Store in a well-ventilated place. Keep container tightly closed.	
Store in a well-ventilated place. Keep cool.	
Store locked up.	
Dispose of contents/container in accordance with local/regional/national/international regula	tions.
• Other hazards	
· Results of PBT and vPvB assessment	
• <i>PBT</i> : Not applicable.	

· vPvB: Not applicable.

3 Composition/information on ingredients

· Chemical characterization: Mixtures

• Description: Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:

142-82-5 aliphatic hydrocarbon	50-100%
541-02-6 decamethylcyclopentasiloxane	2.5-10%

4 First-aid measures

- · Description of first aid measures
- General information: Immediately remove any clothing soiled by the product.
- After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:
- CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam. • For safety reasons unsuitable extinguishing agents: Water with full jet
- Special hazards arising from the substance or mixture No further relevant information available.

(Contd. on page 3)

Printing date 05/07/2019

Reviewed on 05/07/2019

(Contd. of page 2)

Trade name: SYNERGY CERAMIC GLASS COATING

· Advice for firefighters

· Protective equipment: No special measures required.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures** Wear protective equipment. Keep unprotected persons away.
- Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- *Methods and material for containment and cleaning up:* Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to item 13. Ensure adequate ventilation.
- **Reference to other sections** See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

7 Handling and storage

· Handling:

- *Precautions for safe handling Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.*
- *Information about protection against explosions and fires: Keep ignition sources away - Do not smoke. Protect against electrostatic charges.*
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:
- Keep receptacle tightly sealed.
- Store in cool, dry conditions in well sealed receptacles.
- · Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

• Additional information about design of technical systems: No further data; see item 7.

- · Control parameters
- · Components with limit values that require monitoring at the workplace:

The following constituent is the only constituent of the product which has a PEL, TLV or other recommended exposure limit.

At this time, the remaining constituent has no known exposure limits.

142-82-5 aliphatic hydrocarbon

PEL Long-term value: 2000 mg/m³, 500 ppm

- REL Long-term value: 350 mg/m³, 85 ppm Ceiling limit value: 1800* mg/m³, 440* ppm *15-min
- *TLV* Short-term value: 2050 mg/m³, 500 ppm Long-term value: 1640 mg/m³, 400 ppm

• Additional information: The lists that were valid during the creation were used as basis.

(Contd. on page 4)

USA

Printing date 05/07/2019

Reviewed on 05/07/2019

Trade name: SYNERGY CERAMIC GLASS COATING

(Contd. of page 3)

- · Exposure controls
- · Personal protective equipment:

• General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work. Avoid contact with the skin. Avoid contact with the eyes and skin.

• Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

• Eye protection:



Tightly sealed goggles

Information on basic physical and General Information	chemical properties	
Appearance:		
Form:	Fluid	
Color:	According to product specification	
Odor:	Characteristic	
Odor threshold:	Not determined.	
pH-value:	Not applicable	
Change in condition	He determined	
Melting point/Melting range:	Undetermined.	
Boiling point/Boiling range:	98 °C (208.4 °F)	
Flash point:	-94 °C (15.8-24.8 °F)	
Flammability (solid, gaseous):	Not applicable.	
Ignition temperature:	215 °C (419 °F)	
Decomposition temperature:	Not determined.	

Printing date 05/07/2019

Reviewed on 05/07/2019

Trade name: SYNERGY CERAMIC GLASS COATING

	(Contd. of page 4
· Auto igniting:	Product is not selfigniting.
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
· Explosion limits:	
Lower:	1.1 Vol %
Upper:	6.7 Vol %
· Vapor pressure at 20 °C (68 °F):	48 hPa (36 mm Hg)
· Density at 20 °C (68 °F):	0.7142 g/cm ³ (5.96 lbs/gal)
· Relative density	Not determined.
· Vapor density	Not determined.
• Evaporation rate	Not determined.
· Solubility in / Miscibility with	
Water:	Not miscible or difficult to mix.
Partition coefficient (n-octanol/wate	e r): Not determined.
· Viscosity:	
Dynamic:	Not determined
Kinematic at 40 °C (104 °F):	<20.5 mm ² /s
Solvent content:	
Organic solvents:	87.5 %
VOC content:	87.50 %
Solids content:	0.0 %
• Other information	No further relevant information available.

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- · Primary irritant effect:
- on the skin: Irritant to skin and mucous membranes.
- on the eye: No irritating effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:
- The product shows the following dangers according to internally approved calculation methods for preparations:

Irritant

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)

None of the ingredients is listed.

(Contd. on page 6)

USA

Printing date 05/07/2019

Reviewed on 05/07/2019

Trade name: SYNERGY CERAMIC GLASS COATING

(Contd. of page 5)

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

- · Toxicity
- Aquatic toxicity: No further relevant information available.
- Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- *PBT:* Not applicable.
- vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

· Waste treatment methods

· Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

· Uncleaned packagings:

• Recommendation: Disposal must be made according to official regulations.

· UN-Number · DOT, ADR, IMDG, IATA	UN1206
· UN proper shipping name	
$\cdot DOT$	Heptanes
· ADR	1206 HEPTANES mixture, ENVIRONMENTALI
	HAZARDOUS
· IMDG	HEPTANES mixture, MARINE POLLUTANT
·IATA	HEPTANES mixture
· Transport hazard class(es)	
-	
·DOT	
3	
V	3 Flammable liquids

Printing date 05/07/2019

Reviewed on 05/07/2019

Trade name: SYNERGY CERAMIC GLASS COATING

	(Contd. of page
· Label	3
· ADR, IMDG	
· Class · Label	3 Flammable liquids 3
· IATA	
· Class	3 Flammable liquids
· Label	3
· Packing group · DOT, ADR, IMDG, IATA	Π
Environmental hazards:	Product contains environmentally hazardous substance contains aliphatic hydrocarbon
• Marine pollutant:	Symbol (fish and tree)
· Special marking (ADR):	Symbol (fish and tree)
• Special precautions for user	Warning: Flammable liquids
· Danger code (Kemler): · EMS Number:	33 F-E,S-D
· Stowage Category	B
• Transport in bulk according to Annex	II of
MARPOL73/78 and the IBC Code	Not applicable.
Transport/Additional information:	
DOT	
Quantity limitations	On passenger aircraft/rail: 5 L
	On cargo aircraft only: 60 L
ADR	
\cdot Excepted quantities (EQ)	Code: E2 Maximum not quantity non inner packaging, 30 ml
	Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
 - IMDG	
· Limited quantities (LQ)	1L
$\cdot Excepted$ quantities (\widetilde{EQ})	Code: E2
	Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
	Maximum net quantity per outer packaging: 500 ml
UN "Model Regulation":	UN 1206 HEPTANES MIXTURE, 3, II, ENVIRONMENTALL HAZARDOUS

15 Regulatory information

 \cdot Safety, health and environmental regulations/legislation specific for the substance or mixture \cdot Sara

• Section 355 (extremely hazardous substances):

None of the ingredients is listed.

(Contd. on page 8)

USA

Printing date 05/07/2019

Reviewed on 05/07/2019

Trade name: SYNERGY CERAMIC GLASS COATING

	(Contd. of page
Section 313 (Specific toxic chemical listings):	
None of the ingredients is listed.	
TSCA (Toxic Substances Control Act) All ingredients are listed	
Hazardous Air Pollutants	
None of the ingredients is listed.	
Proposition 65	
Chemicals known to cause cancer:	
None of the ingredients is listed.	
Chemicals known to cause reproductive toxicity for females:	
None of the ingredients is listed.	
Chemicals known to cause reproductive toxicity for males:	
None of the ingredients is listed.	
· · ·	
Chemicals known to cause developmental toxicity:	
None of the ingredients is listed.	
Carcinogenic categories	
EPA (Environmental Protection Agency)	
142-82-5 aliphatic hydrocarbon	
TLV (Threshold Limit Value established by ACGIH)	
None of the ingredients is listed.	
NIOSH-Ca (National Institute for Occupational Safety and Health)	
None of the ingredients is listed.	
The product is classified and labeled according to the Globally Harmonized System (G Hazard pictograms	iHS).
Hazard pictograms	(HS).
	HS).
Hazard pictograms GHS02 GHS07 GHS08	HS).
Hazard pictograms	(HS).
Hazard pictograms	HS).
Hazard pictograms	iHS).
Hazard pictograms	iHS).
Hazard pictograms	iHS).
Hazard pictograms Weightson the second seco	iHS).
Hazard pictograms Weightson the second statements Hazard biological statements Hazard statements Highly flammable liquid and vapor. Causes skin irritation. May cause drowsiness or dizziness. May be fatal if swallowed and enters airways. Precautionary statements	iHS).
Hazard pictograms Image: Constraint of the system	iHS).
Hazard pictograms Image: Construction of the system of the syst	iHS).
Hazard pictograms Image: Constraint of the system	iHS).
Hazard pictograms Image: Construction of the system of the syst	iHS).
Hazard pictograms Image: Provide the system of th	iHS).
Hazard pictograms Image: Provide the second state of the seco	iHS).
 Hazard pictograms Azard pictograms Azard pictograms Azard pictograms GHS02 GHS07 GHS08 Signal word Danger Hazard-determining components of labeling: aliphatic hydrocarbon Hazard statements Highly flammable liquid and vapor. Causes skin irritation. May cause drowsiness or dizziness. May be fatal if swallowed and enters airways. Precautionary statements Keep away from heat/sparks/open flames/hot surfaces No smoking. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing dust/fume/gas/mist/vapors/spray Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. 	iHS).
 Hazard pictograms Azard pictograms Azard pictograms Azard pictograms GHS02 GHS07 GHS08 Signal word Danger Hazard-determining components of labeling: aliphatic hydrocarbon Hazard statements Highly flammable liquid and vapor. Causes skin irritation. May cause drowsiness or dizziness. May be fatal if swallowed and enters airways. Precautionary statements Keep away from heat/sparks/open flames/hot surfaces No smoking. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing dust/fume/gas/mist/vapors/spray Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection. 	iHS).
Hazard pictograms $\bigvee \bigvee $	iHS).
 Hazard pictograms A and pi	iHS).
Hazard pictograms $\bigvee \bigcirc \bigvee \bigcirc$	

Printing date 05/07/2019

Reviewed on 05/07/2019

(Contd. of page 8)

USA

Trade name: SYNERGY CERAMIC GLASS COATING

IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell. Take off contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical advice/attention. In case of fire: Use for extinction: CO2, powder or water spray. Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool. Store locked up. Dispose of contents/container in accordance with local/regional/national/international regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Date of preparation / last revision 05/07/2019 / 3

· Abbreviations and acronyms: ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association ACGIH: American Conference of Governmental Industrial Hygienists EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) VOC: Volatile Organic Compounds (USA, EU) PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety OSHA: Occupational Safety & Health TLV: Threshold Limit Value PEL: Permissible Exposure Limit REL: Recommended Exposure Limit Flam. Liq. 2: Flammable liquids - Category 2 Skin Irrit. 2: Skin corrosion/irritation - Category 2 STOT SE 3: Specific target organ toxicity (single exposure) - Category 3 Asp. Tox. 1: Aspiration hazard - Category 1 • * Data compared to the previous version altered.