SECTION 1: *IDENTIFICATION*

Product Name: Triple M Spoke & Chrome Wheel Cleaner Product Use: Automotive Detailing

Manufacturer/Supplier:

Martin Distributors Auto Wax & Polish Inc. 12701 Van Nuys Blvd Ste O Pacoima, CA 91331

Telephone Number: 818 897-8900 FAX Number: 818-897-9288 E-mail: autowax@gmail.com

SECTION 2: HAZARD(S) IDENTIFICATION

GHS Classification:

Health Environmental	Physical
Eye Effects – Category 1 (Serious eye damage) Skin	Flammable Liquid – N/A Explosives – N/A Flammable
Corrosion – Category 1A	Gases – N/A Flammable Aerosols – N/A Oxidizing Gases
Acute Toxicity – Cat 3 (oral)	– N/A Gases Under Pressure – N/A Flammable Solid – N/
Cat 3 (inhalation)	А
Cat 3 (dermal) Skin Sensitization – N/A	Self-reactive substances – N/A Pyrophoric solids – N/A
Mutagenicity – N/A Carcinogenicity- Category 1A	Self-Heating substances – N/A Oxidizing Liquids – N/A
Reproductive/Developmental- N/A Target Organ Toxicity	Oxidizing Solids – N/A Organic Peroxides – N/A
– N/A Toxicity – N/A	Corrosive to Metal – N/A
Aspiration Hazard – N/A Environmental Hazards – N/A Hazardous to the aquatic environment – cat 3	Substances which, in contact with water emit flammable gasses $- N/A$

	Precautionary Statements
	General:
	P101 If medical advice is needed, have product or label at
Hazard Statements	hand. P102 Keep out of reach of children
DANCEDI	P103 Read label before use. <u>Prevention:</u>
DANGER! H200 May be corrective to matche H201 Taxia if swellowed	234 Keep only in original containers.
H290 May be corrosive to metals H301 Toxic if swallowed. H314 Causes severe skin burns and eye damage. H318 Causes	P261 Avoid breathing dust/fumes/mist/vapors/spray. P262 Do not get in eyes, on skin, or on clothing.
serious eye damage.	P264 Wash skin thoroughly after handling.
H331 Toxic if inhaled. H350 May cause cancer	P270 Do not eat, drink or smoke when using this product. P271
	Use only outdoors or in a well-ventilated area.
	P280 Wear Protective gloves/protective clothing/eye protection/
	face protection.
	Response:
	P301+P310+P330 If SWALLOWED: Immediately call a
	POISON CENTER
	or doctor/physician. Rinse mouth.
	P301 + P330+P331 IF SWALLOWED: Rinse mouth. Do NOT
	induce vomiting.
	P303+P361+P353 IF ON SKIN: Remove/Immediately take off
	all contaminated clothing. Rinse skin with water/shower.
	D204, D240, D210 IF INITALED, D
	P304+P340+P310 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
	Immediately call a POISON CENTER or doctor/physician.
	P305+P351+P338+P310 IF IN EYES: Rinse cautiously with
	water for several minutes. Remove contact lenses, if present
	and easy to do. Continue rinsing. Immediately call a POISON
	CENTER or doctor / physician.
	P363 Wash contaminated clothing before reuse. P390 Absorb
	spillage to prevent material damage. Storage:
	spillage to prevent material damage. <u>Storage:</u> P403 Store in a well-ventilated place.
	P405 Store locked up. Keep container tightly closed. P406
	Store in corrosive resistant container.
	Disposal: <u>D501</u> Dispose of contents/container in coordenee with local/
	P501 Dispose of contents/container in accordance with local/ regional/national/international regulations.

SECTION 3: COMPOSITION / INFORMATION ON INGREDIENTS

Component	CAS Number	Weight %
Sulfuric Acid	7664-93-9	≤ 10
Ethylene Glycol Butyl	111-76-2	≤ 10
Ammonium hydrogen Fluoride	1341-49-7	≤ 5
Dodecylbenzen	27176-87-0	≤ 15

SECTION 4: FIRST AID MEASURES

- Eye Contact: Flush immediately with large amounts of clean water for at least 15 minutes; Eyelids should be held away from the eyeball to ensure thorough rinsing. If any irritation persists, seek medical attention.
- Skin Contact: Rinse area with soap and water. Seek medical attention if any redness or irritation persists. Take off immediately all contaminated clothing.
- Inhalation: If breathing is difficult or irritating, move to fresh air immediately. If symptoms persist, get medical attention.
- Ingestion: Rinse mouth. Get immediate medical attention. Give 1% solution in physiological serum (10mL of calcium gluconate 10% in 90 ml of physiological serum. Do not induce vomiting unless directed by medical personnel.

SECTION 5: FIRE FIGHTING MEASURES

Suitable Extinguishing Media: Use dry chemical, foam, or carbon dioxide to extinguish fire. Water may be ineffective but should be used to cool fire-exposed containers, structures and to protect personnel. Use water to dilute spills and to flush them away from sources of ignition.

Fire Fighting Procedures: No special protective action for fire fighters are anticipated.

Unusual Fire and Explosion: Fire or excessive heat may produce hazardous decomposition production.

Combustion Products: Sulfur containing gases. SECTION 6: ACCIDENTAL RELEASE MEASURES

Exposure to the spilled material may be severely irritating or toxic. Follow personal protective equipment recommendations found in Section 8 of this SDS. Personal protective equipment needs must be evaluated based on information provided on this sheet and the special circumstances created by the spill including; the material spilled, the quantity of the spill, the area in which the spill occurred, and the expertise of employees in the area responding to the spill. Never exceed any occupational exposure limits. Prevent the spread of any spill to minimize harm to human health and the environment if safe to do so. Wear complete and proper personal protective equipment following the recommendation of Section 8 at a minimum. Dike with suitable absorbent material like granulated clay. Gather and store in sealed container pending a waste disposal evaluation. Contain spilled liquid with sand or earth. Do not use combustible materials such as sawdust. Use appropriate personal protective equipment as stated in Section 8 of this SDS. Advice the environmental protection agency (EPA) and appropriate state agencies, if required. Absorb spill with inert material (e.g. dry sand or earth), then place in a chemical waste container. Vacuum or sweep up material and place in a disposal container.

SECTION 7: HANDLING AND STORAGE

Handling: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe dust/fumes/gas/mist/vapors/spray. Wash thoroughly after handling. Avoid release to the environment. Wear protective gloves/protective clothing/eye protection/face protection. Use personal protective equipment as required.

Storage: Store locked up. Keep container tightly closed in a cool, well-ventilated place.

Storage Code: White – Corrosive. Separate acids from bases; separate oxidizer acids from organic acids. SECTION 8: EXPOSURE CONTROL / PERSONAL PROTECTION Exposure Limits:

Ammonium hydrogen Fluoride No specific TLV TEL has been set. 1341-49-7

Sulfuric Acid	7664-93-9
PEL (OSHA)	1 mg/m3, 8 Hr. TWA
TLV (ACGIH)	1.2 mg/m3, 8 Hr. TWA

A2 (Sulfuric Acid Contained in strong inorganic acid mists)

Ethylene Glycol Monobutyl

111-76-2

Engineering Controls: Local exhaust ventilation or other engineering controls are normally required when handling or using this product to avoid overexposure.

Personal Protective Equipment (PPE): Lab coat, apron, gloves, goggles, eye wash, safety shower.

Respiratory Protection: Respiratory protection may be required to avoid overexposure when handling this product. General or local exhaust ventilation is the preferred means of protection. Use a respirator if general room ventilation is not available or sufficient to eliminate symptoms.

- Respirator Type(s): None required where adequate ventilation is provided. If airborne concentrations are above the applicable exposure limits, use NIOSH/MSHA approved respiratory protection.
- Eye Protection: Wear chemical splash goggles when handling this product. Have an eye wash station available.
- Skin Protection: Avoid skin contact by wearing chemically resistant gloves, an apron and other protective equipment depending upon conditions of use. Inspect gloves for chemical break-through and replace at regular intervals. Clean protective equipment regularly. Wash hands and other exposed areas with mild soap and water before eating, drinking, and when leaving work.
- Gloves: Natural Latex, Neoprene, Nitrile, Butyl rubber.

SECTION 9: *PHYSICAL AND CHEMICAL PROPERTIES*

Flashpoint:	Not available	Lower Flammability Limit:	No data available
Auto-ignition Temperature:	Not available	Upper Flammability Limit:	No data available
Boiling Point:	100°C	Volatile Organic Compound:	N/A
Melting Point:	No data available	Volatile Organic Compound:	N/A
Vapor Pressure:	<0.3 mm Hg @ 25°C	Evaporation Rate (Water=1):	No data available
Vapor Density $(Air = 1)$:	3.4	Viscosity:	Not available
Solubility:	Yes, water 100%	pH:	3 - 4
Pour Point:	Not available	Molecular Weight:	Mixture
Molecular Formula:	Mixture	Spec. Grav. / Density:	8.805 lbs./gal.
Odor/Appearance:	Pungent acidic / Liquid		

SECTION 10: STABILITY AND REACTIVITY

Reactivity:	This material may be reactive with certain agents under certain conditions.
Chemical Stability:	Stable under normal conditions.
Possibility of hazardous reactions:	Hazardous polymerization will not occur.
Conditions to avoid:	Contact with water. Reaction with water is exothermic.
Incompatible materials:	Water-reactive materials, water, organic compounds, strong reducing agents,
	Acetaldehydes, Amines
Hazardous Decomposition:	None know.

SECTION 11: TOXICOLOGICAL INFORMATION

Signs and Systems of Exposure: Based on the test data and/or information on the components, this material may produce the following health effects:

Inhalation: Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

Skin Contact: Mild Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, and dryness. Allergic Skin Reaction (non-photo induced) in sensitive people: Signs/symptoms may include redness, swelling, blistering, and itching.

Eye Contact: Moderate Eye Irritation: Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

Ingestion: Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

Target Organ Effects: Allergic Skin Reaction (non-photo induced) in sensitive people. Signs/symptoms may include redness, swelling, blistering, and itching.

Toxicological Data: If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Theute Toxicity			
Name	Route	Species	Value
Sulfuric Acid	Oral	Rat	LD 50 2,140 mg/kg
Sulfuric Acid	Inhalation	Guinea Pig	LC 50 30mg/m3
Sulfuric Acid	Dermal	-	Not available
Ammonium hydrogen Fluoride	Oral	Rat	LD 50 60 – 130 mg/kg
Ammonium hydrogen Fluoride	Inhalation	-	Not available
Ammonium hydrogen Fluoride	Dermal	-	Not available
Ethylene Glycol Butyl	Oral	Guinea Pig	LD 50 1,200 mg/kg
Ethylene Glycol Butyl	Inhalation	Guinea Pig	LD 50 >633ppm, 1h.
Ethylene Glycol Butyl	Dermal	Guinea Pig	LD 50 >2,000 mg/kg
Dodecylbenzen	Oral	Rabbit	LD 50: 1407 mg/kg
Dodecylbenzen	Inhalation	_	No data available

Acute Toxicity

Dodecylbenzen	Dermal	-	No data available	
Skin Corrosion/Irritation				
Name	Route	Species	Value	
Serious Eye Dama		Spacios	Value	
Name	Route	Species	Value	
Skin Sensitization				
Name	Route	Species	Value	
Respiratory Sensit			X 1	
Name	Route	Species	Value	
Germ Cell Mutage	enicity			
Name	Route	Species	Value	
	L.	· ▲	L	
Carcinogenicity			1	
Name	Route	Species	Value	
<u>+</u>	or Developmental Effects	1 ~ ·		
Name	Route	Species	Value	
Target Organ (s)				
	gan Toxicity – Single Exposure		X7.1	
Name	Route	Species	Value	
Specific Target Organ Toxicity – repeated exposure				
Name	Route	Species	Value	
Ammonium hydrogen	Oral	Rat	Liver, Testes, skeleton,	
Fluoride			thyroid, NOEL: 1 mg/kg	
Aspiration Hazard				
Name	Route	Species	Value	
Mobility: This material is e	<u>CAL INFORMATION</u> gical hazard. This product may expected to have high mobility i n, adsorption to sediment, and b	n soil. It absorbs weakly to mos	st soil types.	
significant.				

Bioaccumulation: Bioconcentration is not expected to occur. Degradability: Does not biodegrade readily. Other Adverse Effect: No Data

Chemical Nam	<u>CAS #</u>	ECO Toxicity

Sulfuric Acid	7664-93-9	96 HR LC50 BRACHYDANIO RERIO> 500MG/L
		24 HR EC50 DAPHNIA MAGNA 29 MG/L

SECTION 13: DISPOSAL CONSIDERATIONS

Disposal Methods: Dispose of in accordance with local, state, and federal regulations. Always contact a permitted waste disposer TSD to assure compliance.

Waste Disposal Code(s): If discarded, this product is considered a RCRA corrosive waste, D002.

SECTION 14: TRANSPORT INFORMATION

Because this is produced and shipped in several different sizes as well as domestically and internationally, please consult your transportation specialist for the proper shipping name and class.

SECTION 15: REGULATORY INFORMATION

Hazard Categories: Fire Hazard – No, Pressure Hazard – No, Reactivity Hazard – No, Immediate Hazard – Yes, Delayed Hazard – Yes

SECTION 16: OTHER INFORMATION

NFPA Hazardous Classification

Health: 3 Flammability: 0 Instability: 0 Special Hazard: None

Revision Indicator: SDS Revision # 3 / Issued January 19, 2015